

Title (en)  
Ski binding.

Title (de)  
Skibindung.

Title (fr)  
Fixation de ski.

Publication  
**EP 0255910 A2 19880217 (EN)**

Application  
**EP 87110887 A 19870728**

Priority  
IT 8256786 A 19860804

Abstract (en)  
The binding comprises a front element (4) for the coupling of the boot and a rear device (5) for the removable locking of the boot. The locking device is provided with sliding elements for its translatory motion, against and due to the biasing action of a first elastic member, along the longitudinal axis of the ski (3) and with rotation elements for its oscillation against and due to, the biasing action of a second elastic member, about an axis which is substantially vertical with respect to the base plate (2). The sliding and rotation elements being structured so as to act independently and simultaneously with respect to one another. The boot has a recess in the sole adapted to engage with the front coupling element (4) and being spaced equidistant from the heel regardless of the size of the boot.

IPC 1-7  
**A43B 5/04; A63C 9/084**

IPC 8 full level  
**A63C 9/00** (2012.01); **A63C 9/08** (2012.01); **A43B 5/04** (2006.01); **A63C 9/081** (2012.01); **A63C 9/084** (2012.01); **A63C 9/085** (2006.01); **A63C 9/086** (2012.01)

CPC (source: EP)  
**A63C 7/1013** (2013.01); **A63C 9/005** (2013.01); **A63C 9/0805** (2013.01); **A63C 9/081** (2013.01); **A63C 9/0842** (2013.01); **A63C 9/0844** (2013.01); **A63C 9/0845** (2013.01); **A63C 9/0846** (2013.01); **A63C 9/086** (2013.01)

Cited by  
US6554295B2

Designated contracting state (EPC)  
AT CH DE FR IT LI

DOCDB simple family (publication)  
**EP 0255910 A2 19880217; EP 0255910 A3 19891011; EP 0255910 B1 19930303**; AT E86134 T1 19930315; DE 3784405 D1 19930408; DE 3784405 T2 19930609; IT 1205520 B 19890323; IT 8682567 A0 19860804; JP S6340583 A 19880220

DOCDB simple family (application)  
**EP 87110887 A 19870728**; AT 87110887 T 19870728; DE 3784405 T 19870728; IT 8256786 A 19860804; JP 19053687 A 19870731