

Title (en)
SAFETY SKI BINDING

Publication
EP 0257073 B1 19891004 (DE)

Application
EP 87901440 A 19870214

Priority
AT 40886 A 19860217

Abstract (en)
[origin: WO8704941A1] Safety ski binding, in particular a heel support (2, 102) with a base plate (3, 103) to be secured to the upper surface of the ski and carrying a vertical rotary pin (4, 104). The heel support (2, 102) is provided with a sole support (6, 106) which can be pivoted upwards against a releasable catch and with a support plate (8, 108) which can pivot around a vertical axis, for the heel (10a) of the ski-boot (10, 110). The support plate (8, 108) is subjected to the pressure of a spring (121) in its central position. In order to be able, in such a ski binding, to locate the rotation axis for the ski-boot (10, 110) roughly in the extension of the tibia and at the same time simplify the design of the ski binding, it is proposed that the rotary pin (4), when viewed in the longitudinal direction of the ski, is located between the front jaw (5) and heel support (2), that the support plate (8) is pivotally supported on the rotary pin (4). By means of a guide mechanism formed of a roller (155) and guide curve (156) the heel support (102) is opened in a horizontal release process. According to the invention, the roller (155) is supported by means of its axis running in the longitudinal direction of the ski in the base plate (103), which cooperates with a guide element (156) which can actuate the releasable catch of the heel support (102). In addition, the support plate (8') can also be designed as a sole plate.

IPC 1-7
A63C 9/081

IPC 8 full level
A63C 9/00 (2006.01); **A63C 9/081** (2006.01); **A63C 9/082** (2006.01); **A63C 9/084** (2006.01); **A63C 9/086** (2006.01); **A63C 9/08** (2006.01); **A63C 9/085** (2006.01)

CPC (source: EP US)
A63C 9/001 (2013.01 - EP US); **A63C 9/081** (2013.01 - EP US); **A63C 9/0844** (2013.01 - EP US); **A63C 9/0847** (2013.01 - EP US); **A63C 9/086** (2013.01 - EP US); **A63C 9/0805** (2013.01 - EP US); **A63C 9/0845** (2013.01 - EP US); **A63C 9/0855** (2013.01 - EP US)

Designated contracting state (EPC)
CH DE FR LI

DOCDB simple family (publication)
WO 8704941 A1 19870827; AT 385421 B 19880325; AT A40886 A 19870915; EP 0256107 A1 19880224; EP 0256107 B1 19900502; EP 0257073 A1 19880302; EP 0257073 B1 19891004; EP 0259407 A1 19880316; EP 0259407 B1 19910327; JP H0362115 B2 19910924; JP H0363919 B2 19911003; JP H0365990 B2 19911015; JP S63500358 A 19880212; JP S63502164 A 19880825; JP S63502406 A 19880914; US 4804202 A 19890214; US 4858946 A 19890822; US 4892326 A 19900109; WO 8704939 A1 19870827; WO 8704940 A1 19870827

DOCDB simple family (application)
EP 8700082 W 19870214; AT 40886 A 19860217; EP 8700080 W 19870214; EP 8700081 W 19870214; EP 87901440 A 19870214; EP 87901441 A 19870214; EP 87901442 A 19870214; JP 50151787 A 19870214; JP 50165687 A 19870214; JP 50166187 A 19870214; US 11672987 A 19871201; US 11673087 A 19871130; US 13838287 A 19871201