

Title (en)
VACUUM DEWATERING INSTALLATION

Publication
EP 0258525 A3 19881005 (DE)

Application
EP 87104283 A 19870324

Priority
DE 3628725 A 19860823

Abstract (en)
[origin: EP0258525A2] 1. A vacuum drainage installation having one or more collection tanks in which an underpressure prevails and to which are connected vacuum conduits (10) which are laid alternately ascending and descending and to which connecting ducts of the units to be drained are connected via a respective extraction valve, normal pressure prevailing in said connecting ducts, which extraction valve is opened automatically when a given amount of water of from 5 to 40 litres has accumulated upstream thereof, and which during each opening operation admits air together with the waste water into the vacuum conduit (10), wherein at least one venting aperture (34), which is controlled by a control device as a function of the water level or pressure at a given location of the vacuum conduit (10), is provided in the vacuum conduit (10), characterised in that the aperture width of the venting aperture (34) can be controlled continuously or in a plurality of stages within a range in which such small quantities of air are admitted that said air bubbles through water columns present in the vacuum conduit (10).

IPC 1-7
E03F 1/00

IPC 8 full level
E03F 1/00 (2006.01)

CPC (source: EP)
E03F 1/006 (2013.01)

Citation (search report)

- [AD] DE 2637962 A1 19780302 - ELECTROLUX GMBH
- [A] US 4500035 A 19850219 - KURODA SHIGEAKI [JP], et al
- [AD] US 3730884 A 19730501 - BURNS B, et al

Cited by
AU766451B2; US6298870B1; WO9957386A1

Designated contracting state (EPC)
AT BE CH DE FR GB LI NL SE

DOCDB simple family (publication)
EP 0258525 A2 19880309; EP 0258525 A3 19881005; EP 0258525 B1 19900606; AT E53415 T1 19900615; DE 3628725 A1 19880225; DE 3763090 D1 19900712

DOCDB simple family (application)
EP 87104283 A 19870324; AT 87104283 T 19870324; DE 3628725 A 19860823; DE 3763090 T 19870324