

Title (en)

DOOR STAY ESPECIALLY FOR AUTOMOBILE DOORS

Publication

EP 0259540 A3 19900328 (DE)

Application

EP 87104673 A 19870330

Priority

DE 3630463 A 19860906

Abstract (en)

[origin: EP0259540A2] On a door stay for motor vehicle doors, whose door catch bar is over mounted by means of a rivet or bolt-on a carrier formed by a moulded part, it is proposed, in order to optimise the design of components and reduce the manufacturing costs, to apply a spring load coaxially to the axis of the bearing of the door catch bar and at the same time to give the rivet or the bolt a circumferential profile which can be deformed in a manner known per se, particularly in the form of a so-called knurl, over part of its length. <IMAGE>

IPC 1-7

B60J 5/00

IPC 8 full level

B60J 5/04 (2006.01); **E05B 49/00** (2006.01); **E05C 17/04** (2006.01); **E05C 17/22** (2006.01)

CPC (source: EP)

E05C 17/045 (2013.01)

Citation (search report)

- [A] DE 3207922 C1 19831013 - OPEL ADAM AG
- [A] US 1696936 A 19290101 - BRENEMAN PAUL E

Cited by

CN115405175A

Designated contracting state (EPC)

ES FR GB IT SE

DOCDB simple family (publication)

EP 0259540 A2 19880316; **EP 0259540 A3 19900328**; **EP 0259540 B1 19920930**; AU 7656387 A 19880310; BR 8701927 A 19880412;
CA 1305594 C 19920728; ES 2034974 T3 19930416; JP H083300 B2 19960117; JP S6370788 A 19880330

DOCDB simple family (application)

EP 87104673 A 19870330; AU 7656387 A 19870803; BR 8701927 A 19870423; CA 546232 A 19870904; ES 87104673 T 19870330;
JP 13004587 A 19870528