

Title (en)
GUIDE FOR A LOCK DRIVE BAR MADE OF A FLAT BAND

Publication
EP 0261265 B1 19900509 (DE)

Application
EP 86113170 A 19860925

Priority
EP 86113170 A 19860925

Abstract (en)
1. Bar guideway for the flat strip bar (18) of a bar closure (14) which is provided, in particular for installation in the fillet gap (10) of sheet metal cabinet doors (12) and in which the flat strip bar (18) carries locking means such as pins, hooks, roll pins or double roll pins (40) which cannot be disassembled or can only be disassembled with difficulty, characterised in that the bar guideway (20) consists of a one-piece, L-shaped corner member (60) of resiliently elastic material, such as synthetic material, on one leg (62) of which a fastening hole (64) is arranged and on the other leg (66) of which there is provided in each case on the outer side at its free edge (68) and in the angle region (70) between the two legs a projecting rail (72 or 74), which has a hook-shaped profile, for guiding the flat strip bar (18).

IPC 1-7
E05C 9/00

IPC 8 full level
E05C 9/00 (2006.01); **E05C 9/22** (2006.01)

CPC (source: EP US)
E05C 9/22 (2013.01 - EP US); **Y10T 292/0843** (2015.04 - EP US); **Y10T 292/1018** (2015.04 - EP US); **Y10T 292/62** (2015.04 - EP US)

Cited by
DE102007001340A1; EP1790807A3; DE4013441C2; DE112006002376B4; DE19503064C1; EP0725200A1; EP2586942A3; DE102008014124A1; DE102008014124B4; DE202007009997U1; DE202008005452U1; DE202008005453U1; WO2007033714A1; WO2008080874A3

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
EP 0261265 A1 19880330; EP 0261265 B1 19900509; DE 3671063 D1 19900613; US 5044677 A 19910903; WO 9205329 A1 19920402

DOCDB simple family (application)
EP 86113170 A 19860925; DE 3671063 T 19860925; DE 8700412 W 19870912; US 21473288 A 19880525