

Title (en)

Lock, especially for an automotive vehicle.

Title (de)

Schloss, insbesondere für Kraftfahrzeuge.

Title (fr)

Serrure perfectionnée, notamment pour véhicule automobile.

Publication

EP 0262051 A1 19880330 (FR)

Application

EP 87402139 A 19870924

Priority

FR 8613493 A 19860926

Abstract (en)

[origin: EP0262051B1] 1. A latch for securing two parts (2, 5) which are moveable relative to one another, notably in a motor vehicle, comprising on the one hand a keeper (4) integral with one of these parts (2, 5) and on the other hand, a casing (1), integral with the other of these parts (2, 5), said casing comprising a bolt (3) which has hooking means consisting of a hook (6) and an inclined surface (6a) adapted to cooperate with said keeper (4) and said bolt being mounted so as to be moveable between an active position towards which it is resiliently urged and in which it extends over the path of displacement of the keeper (4), and a retracted position, to permit the hooking or release of the keeper (4) and on the other hand between a position of hooking (A) of the keeper (4) in which the latter is hooked on the bolt (3) by manual actuation of one of the these parts (2, 5) and a position of locking (B) of the keeper (4), the movement between these positions of hooking (A) and locking (B) taking place substantially parallel to the parts of the keeper (4) in the vicinity of the casing (1) and with the aid of actuating means (7) which are controlled either by the reciprocal hooking of the keeper (4) and bolt (3) in the hooking position (A) to move them into the locking position (B) or by actuation of the means for releasing the bolt (3) in the locking position (B) in order to move it into the hooking position (A), and retracting means (8) consisting of an abutment member (9) mounted so as to be moveable on the casing (1) between an active position towards which it is resiliently biased and a retracted position and abutment surfaces (9a, 9b) adapted to cooperate with bearing surfaces (3a, 3b) of the bolt (3), so that when the bolt (3) moves towards its locking position (B) the abutment member (9) assumes its retracted position as a result of contact between the abutment surface (9a) and bearing surface (3b), said latch being characterized in that the casing (1) is provided with an abutment surface (1b) adapted to cooperate with the abutment surfaces (9a, 9b) so that when the bolt (3) moves towards its hooking position (A) it moves towards its retracted position for releasing the keeper (4) by contact between the abutment surfaces (9a, 9b) and abutment surface (1b), and in that the bearing surfaces (3a, 3b) are fixed to the bolt (3) and in that said latch comprises a slide member (10) which is moveably mounted in the casing (1) and which is moved by the actuating means (7), in that the bolt (3) is generally in the form of an S, one end of which comprises the hooking means (6, 6a) whilst the other end comprises the bearing surfaces (3a, 3b) and the central part is articulated on the slide member (1), in that the actuating means (7) comprise a motor-speed reducer (13) acting on drive means (14) connected to the slide member (10).

Abstract (fr)

Cette serrure comportant un boîtier (1), solidaire d'une première partie (2) du véhicule, et dans lequel est disposé un pène (3), et une gâche (4) solidaire d'une seconde partie (5) du véhicule, et adaptée pour coopérer avec ledit pène, lesdites première et seconde parties du véhicule étant mobiles l'une par rapport à l'autre et le pène (3) étant monté déplaçable entre une position de libération de la gâche et une position de verrouillage de celle-ci dans le boîtier (1), est caractérisée en ce que le pène comprend des moyens d'accrochage (6) de la gâche et est monté déplaçable le long d'un trajet à peu près parallèle au trajet de déplacement de la gâche (4) au voisinage du boîtier (1), entre une position d'accrochage (A) de la gâche, l'accrochage étant réalisé par manoeuvre de ladite partie mobile du véhicule par l'utilisateur et la position de verrouillage (B) de la gâche, par l'intermédiaire de moyens d'actionnement (7) commandés dans un sens, par des moyens d'indication de la présence de la gâche en position d'accrochage (A) et dans l'autre sens, par des moyens d'indication de l'actionnement de moyens de déverrouillage du pène (3).

IPC 1-7

E05B 17/00

IPC 8 full level

E05B 65/12 (2006.01)

CPC (source: EP US)

E05B 81/20 (2013.01 - EP US); **Y10T 292/0914** (2015.04 - EP US); **Y10T 292/1082** (2015.04 - EP US)

Citation (search report)

[X] US 3321226 A 19670523 - DE CLAIRE JAMES H, et al

Designated contracting state (EPC)

DE ES GB IT SE

DOCDB simple family (publication)

EP 0262051 A1 19880330; EP 0262051 B1 19891220; DE 3761217 D1 19900125; ES 2012095 B3 19900301; FR 2604473 A1 19880401;
FR 2604473 B1 19920612; US 4951979 A 19900828

DOCDB simple family (application)

EP 87402139 A 19870924; DE 3761217 T 19870924; ES 87402139 T 19870924; FR 8613493 A 19860926; US 31422289 A 19890221