

Title (en)

Apparatus for the incineration of waste.

Title (de)

Vorrichtung zur Veraschung von Abfällen.

Title (fr)

Dispositif d'incinération de déchets.

Publication

EP 0262315 A2 19880406 (DE)

Application

EP 87109951 A 19870710

Priority

DE 3632548 A 19860925

Abstract (en)

1. Cylindrical rotary furnace for the degasification and incineration of waste material, the degasification taking place in a pyrolysis drum, which comprises a feed opening for the waste material, to which a low-temperature carbonisation gas outlet is connected and the incineration taking place in a combustion drum mounted in a rotary manner, which at the feed end comprises a waste gas outlet and at the discharge end for the ashes comprises a burner, characterised in that a) the pyrolysis drum (2) is located inside the combustion drum (1) and connected thereto in a non-rotary manner, which drum forms an annular chamber (27) between itself and the combustion drum and which, starting from the feed end, extends in the direction of the discharge end over a partial length of the combustion drum (1), b) at its end projecting into the combustion drum (1), the pyrolysis drum (2) comprises a discharge opening (16) for low-temperature coke formed from the waste material, which is burnt to ashes in the adjoining combustion chamber (15) of the combustion drum (1), and c) the annular chamber (27) between the combustion drum (1) and the pyrolysis drum (2) is connected to the waste gas outlet (7).

Abstract (de)

Bei einem Verfahren zur Veraschung von Abfällen in einem Drehrohrofen mit einer indirekt beheizten Pyrolysetrommel (2), in welcher die Abfälle unter Erzeugung von Schwelgas zu Schwelkoks verschwelt werden, ist zur Förderung der Energieausnutzung vorgesehen, daß der Schwelkoks aus der Pyrolysetrommel (2) in einem von einem Brenner (19) beheizten Verbrennungsraum (15) zu Asche verbrannt wird, und daß die Rauchgase zur indirekten Beheizung der Pyrolysetrommel (2) verwendet werden, bevor sie in einer Nachbrennkammer verbrannt werden, in welche das Schweißgas zwecks Reduzierung der Brennerenergie für die Nachbrennkammer eingeleitet und direkt verbrannt wird.

IPC 1-7

F23G 5/027

IPC 8 full level

F23G 5/027 (2006.01); **F23G 5/20** (2006.01)

CPC (source: EP)

F23G 5/0273 (2013.01)

Cited by

GB2350370A; ES2259268A1; EP0360052A1

Designated contracting state (EPC)

AT CH FR GB LI NL

DOCDB simple family (publication)

EP 0262315 A2 19880406; EP 0262315 A3 19890111; EP 0262315 B1 19900509; AT E52604 T1 19900515; DE 3632548 C1 19871015

DOCDB simple family (application)

EP 87109951 A 19870710; AT 87109951 T 19870710; DE 3632548 A 19860925