

Title (en)  
METHOD OF FORMING WEATHERTIGHT SEAL

Publication  
**EP 0262968 A3 19890531 (EN)**

Application  
**EP 87308710 A 19871001**

Priority  
US 91391686 A 19861001

Abstract (en)  
[origin: EP0262968A2] A method of forming a weathertight seal between surfaces (1,2) which move in relation to each other during the time required for the seal to be applied and cured is disclosed. The seal is formed from a preformed silicone gasket (3) which is bonded in place with a silicone adhesive (4). The silicone adhesive (4) bonds rapidly and cures because it is either a pressure sensitive adhesive, a two part adhesive which cures rapidly, or is a moisture-curable adhesive which cures rapidly because it is a thin layer in contact with a silicone elastomer, said elastomer being permeable to moisture.

IPC 1-7  
**E04B 1/68**

IPC 8 full level  
**E04B 1/62** (2006.01); **E04B 1/68** (2006.01); **E04B 1/682** (2006.01); **E04B 1/684** (2006.01); **E06B 3/54** (2006.01)

CPC (source: EP)  
**E04B 1/6815** (2013.01); **E06B 3/5427** (2013.01)

Citation (search report)

- [XD] DE 3131677 A1 19830224 - HAGEN PERENNATORWERK [DE]
- [AD] US 3829228 A 19740813 - MIYAZAKI N, et al
- [X] DAS BAUZENTRUM-SEMINAR, BAUTECHNISCHE ERFAHRUNGEN MIT KUNSTSTOFFEN. vol. 7, May 1972, pages 59-71, Darmstadt, DE; H. GOETZE: "Fugendichtung, Fassaden-Imprägnierung".
- [X] BETON- UND STAHLBETONBAU. June 1974, pages A15, A16, Berlin, DE; LECHLER CHEMIE GMBH: "Fugendichten mit neuen Produkten".

Cited by  
US5765332A; CN115306263A; EP0529546A1; US5300171A; WO9626332A1

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**EP 0262968 A2 19880406; EP 0262968 A3 19890531**; CA 1301438 C 19920526; JP S6389756 A 19880420

DOCDB simple family (application)  
**EP 87308710 A 19871001**; CA 543394 A 19870730; JP 21554987 A 19870831