

Title (en)

OPTICAL SORTING DEVICE TO SEPARATE TWO CATEGORIES OF PARTICLES HAVING DIFFERENT OPTICAL TRANSMISSIVITIES

Publication

EP 0263015 A3 19880622 (FR)

Application

EP 87402095 A 19870921

Priority

FR 8613511 A 19860929

Abstract (en)

[origin: EP0263015A2] The particles to be sorted are poured onto a translucent inclined plane (3) beneath which is arranged a light source and above which is placed a camera. At the bottom of the inclined plane (3) there are arranged, side by side, hammers (8) capable of tilting about a pivot (9) between a rest position and a position in which they eject the undesirable particle when the latter is detected by the camera. Each hammer (8) is fixed to a connecting rod (47), the downwards displacement of which places the hammer (9) in the ejection position. The connecting rod (47) is joined to the rod (61) of a double-action pneumatic jack (62) controlled by a distributor (43) which is pilot-controlled by a light-sensitive element of the camera. Applicable for sorting cullet. <IMAGE>

IPC 1-7

B07C 5/36; B07C 5/34

IPC 8 full level

B07C 5/34 (2006.01); **B07C 5/36** (2006.01)

CPC (source: EP)

B07C 5/3416 (2013.01); **B07C 5/362** (2013.01)

Citation (search report)

- [YD] FR 2576008 A1 19860718 - BSN [FR]
- [Y] US 2927690 A 19600308 - DAVID MALMQVIST JOHAN, et al

Cited by

CN114833096A; US5603413A; FR2632879A1; CN110624856A; AU2010285188B2; AU2010285188C1; US5314072A; US8803020B2; WO2011020628A1; WO9505249A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

EP 0263015 A2 19880406; EP 0263015 A3 19880622; EP 0263015 B1 19910403; AT E62155 T1 19910415; DE 3769058 D1 19910508; FR 2604377 A1 19880401; FR 2604377 B1 19900420

DOCDB simple family (application)

EP 87402095 A 19870921; AT 87402095 T 19870921; DE 3769058 T 19870921; FR 8613511 A 19860929