

Title (en)
SECURITY CAP FOR CLOSING FLASKS OR THE LIKE

Publication
EP 0265295 B1 19900207 (FR)

Application
EP 87401880 A 19870813

Priority
FR 8612919 A 19860916

Abstract (en)
[origin: US4779747A] The neck of a flask has an upper portion with a thread adapted for cooperating with an internal thread of a cylindrical screw cap. The cap has a lower portion carrying a radial male key which bears on a lower portion of the neck of the flask when the cap is screwed onto said neck; at least two concentric annuluses are held by an inner ring in a cylindrical groove of the flask, and also in a groove formed in an upper portion of the lower annulus for the mobile annulus. The two annuluses are each formed with a walled passage for disengagement of the radial male key when the cap is unscrewed from the neck of the flask. The screw cap and the concentric annuluses each having a guiding mark for vertical alignment of the male key and the walled passages.

IPC 1-7
B65D 55/02

IPC 8 full level
B65D 41/04 (2006.01); **B65D 50/06** (2006.01); **B65D 55/02** (2006.01); **B65D 55/14** (2006.01)

CPC (source: EP US)
B65D 50/062 (2013.01 - EP US); **B65D 55/145** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH DE ES GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0265295 A1 19880427; **EP 0265295 B1 19900207**; AT E50225 T1 19900215; DE 3761647 D1 19900315; ES 2012496 B3 19900401; FR 2603871 A1 19880318; FR 2603871 B1 19881202; JP S6382956 A 19880413; US 4779747 A 19881025

DOCDB simple family (application)
EP 87401880 A 19870813; AT 87401880 T 19870813; DE 3761647 T 19870813; ES 87401880 T 19870813; FR 8612919 A 19860916; JP 22993287 A 19870916; US 8801587 A 19870818