

Title (en)

SILVER HALIDE PHOTOGRAPHIC LIGHT-SENSITIVE MATERIAL CAPABLE OF SUPER-RAPID PROCESSING

Publication

**EP 0267019 A3 19890719 (EN)**

Application

**EP 87309756 A 19871104**

Priority

- JP 26229586 A 19861104
- JP 29849986 A 19861215

Abstract (en)

[origin: EP0267019A2] A silver halide photographic light-sensitive material comprising a support having the first photographic structural layer comprising one or more layers on a side of the support and the second photographic structural layer comprising one or more layers on the other side of the support, in which at least one of the photographic structural layers comprises a silver halide light-sensitive emulsion layer, and the total amount of gelatin contained in the photographic structural layer comprising the silver halide emulsion layer is within the range of from 2.00 g/m<sup>2</sup> to 3.50 g/m<sup>2</sup>. The uppermost layer of the photographic structural layer comprising the silver halide emulsion is formed by coating of a solution having a surface tension of from 15 to 26 dyn/cm, and the second photographic structural layer is coated and gelled between coating and drying of the first photographic structural layer. The photographic material is improved in the adaptability for super-rapid processing with the total duration of 20 to 60 sec. and the anti-scratch property.

IPC 1-7

**G03C 1/46**; **G03C 1/02**; **G03C 1/38**; **G03C 1/74**

IPC 8 full level

**B05C 5/00** (2006.01); **G03C 1/005** (2006.01); **G03C 1/38** (2006.01); **G03C 1/46** (2006.01); **G03C 1/74** (2006.01); **G03C 5/16** (2006.01); **B05C 9/04** (2006.01); **G03C 1/18** (2006.01); **G03C 1/95** (2006.01)

CPC (source: EP US)

**B05C 5/007** (2013.01 - EP US); **G03C 1/005** (2013.01 - EP US); **G03C 1/38** (2013.01 - EP US); **G03C 1/46** (2013.01 - EP US); **G03C 1/74** (2013.01 - EP US); **G03C 5/16** (2013.01 - EP US); **B05C 9/04** (2013.01 - EP US); **G03C 1/18** (2013.01 - EP US); **G03C 1/95** (2013.01 - EP US); **G03C 2001/7425** (2013.01 - EP US); **G03C 2200/52** (2013.01 - EP US)

Citation (search report)

- [Y] GB 2114309 A 19830817 - KONISHIROKU PHOTO IND
- [Y] EP 0093177 A1 19831109 - KONISHIROKU PHOTO IND [JP]
- [Y] EP 0111338 A2 19840620 - DU PONT [US]
- [Y] EP 0118793 A2 19840919 - KONISHIROKU PHOTO IND [JP]
- [Y] PATENT ABSTRACTS OF JAPAN, vol. 10, no. 300 (P-506)[2356], 14th october 1986; & JP-A-61 116 349 (KONISHIROKU PHOTO IND. CO. LTD) 03-06-1986

Cited by

EP0620482A1; US4946769A; EP0566374A3; EP0620483A1; EP0450977A3; EP0366418A3; EP0620484A1; EP0747760A1; EP0670517A3; US5516627A; EP0706081A1; FR2725536A1; US5773204A; US5230994A

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

**EP 0267019 A2 19880511**; **EP 0267019 A3 19890719**; **EP 0267019 B1 19950419**; DE 3751257 D1 19950524; DE 3751257 T2 19951116; US H674 H 19890905

DOCDB simple family (application)

**EP 87309756 A 19871104**; DE 3751257 T 19871104; US 11622987 A 19871103