

Title (en)  
LOCK WITH A ROTOR CONNECTED TO THE BOLT BY A SET OF PINIONS

Publication  
**EP 0270425 B1 19900620 (FR)**

Application  
**EP 87402536 A 19871110**

Priority  
FR 8616376 A 19861125

Abstract (en)  
[origin: EP0270425A2] 1. Cylinder lock comprising a first pinion (6) provided with a radial slot (19) for axial engagement of a cylinder body (11) carrying a movable bit (15) which is adapted to drive said first pinion about its axis while being inserted with play within the slot between two actuating teeth (17-18) of greater width than the other teeth (22) of said first pinion and disposed on each side of said slot (19), said actuating teeth (17-18) being of greater thickness than said pinion and forming projections on one of the faces of this latter, and a second pinion (7) in cooperating relation with the first and having two receiving teeth (24-25) of greater width than the other teeth (23) of said second pinion, these receiving teeth (24-25) being separated by a free space (26) having a width substantially equal to that of the slot (19) of said first pinion, characterized in that said second pinion (7) is provided in its plane on each side of the receiving teeth and opposite to said free space with two complementary extensions (29-30) adapted to cooperate without play with two recesses (20-21) formed in said first pinion in the plane of this latter.

IPC 1-7  
**E05B 17/04**

IPC 8 full level  
**E05B 17/04** (2006.01)

CPC (source: EP)  
**E05B 17/042** (2013.01)

Cited by  
FR2707322A1; GB2272247A; DE19650136B4; FR3008123A1; EP0906996A3; ITNO20100002A1; GB2338264A; AU719921B2; GB2338264B; FR2690944A1; US6374650B1; FR2708305A1; GB2274306A; FR2704264A1; GB2274306B; BE1008364A5; DE4400473C2; WO9845558A1; EP0906996A2

Designated contracting state (EPC)  
BE DE ES GB IT

DOCDB simple family (publication)  
**EP 0270425 A2 19880608; EP 0270425 A3 19880706; EP 0270425 B1 19900620**; DE 3763325 D1 19900726; ES 2016858 B3 19901201; FR 2607176 A1 19880527; FR 2607176 B1 19890331

DOCDB simple family (application)  
**EP 87402536 A 19871110**; DE 3763325 T 19871110; ES 87402536 T 19871110; FR 8616376 A 19861125