

Title (en)
Shuttering for concrete work.

Title (de)
Betonierungsschalung.

Title (fr)
Coffrage pour bétonnage.

Publication
EP 0274133 B1 19940914 (DE)

Application
EP 87119380 A 19871230

Priority
DE 3700429 A 19870108

Abstract (en)
[origin: EP0274133A2] The supporting section (6) has a first flange region (8), a second flange region (10) and a web (12) between the two flange regions (8, 10), and a plurality of longitudinally spaced holes are provided respectively in the web (12) in the end regions of the supporting section (6). The supporting section (6) is provided, in the web (12), continuously over the length both with a row of long holes (16), spaced at a grid dimension (a) for receiving a wedge, and, at least on one side of the row of long holes with a row of holes (18; 2) spaced at a grid dimension (a), the grid dimension (a) of the row of long holes and the grid dimension (a) of the at least one row of holes each being essentially an integral fraction of the length of the supporting section.

IPC 1-7
E04G 9/00; E04G 11/50; E04C 3/09

IPC 8 full level
E04C 3/09 (2006.01); **E04G 9/00** (2006.01); **E04G 11/50** (2006.01); **E04C 3/04** (2006.01)

CPC (source: EP)
E04C 3/09 (2013.01); **E04G 11/50** (2013.01); **E04C 2003/0413** (2013.01); **E04C 2003/0421** (2013.01); **E04C 2003/0434** (2013.01); **E04C 2003/0452** (2013.01); **E04C 2003/0473** (2013.01)

Cited by
CN110469052A; CN100436738C; DE102009032423B4; EP3075924A1; WO2016156444A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB IT LI

DOCDB simple family (publication)
EP 0274133 A2 19880713; **EP 0274133 A3 19890201**; **EP 0274133 B1 19940914**; AT E111551 T1 19940915; DE 3700429 A1 19880728; DE 3750545 D1 19941020; ES 2063736 T3 19950116

DOCDB simple family (application)
EP 87119380 A 19871230; AT 87119380 T 19871230; DE 3700429 A 19870108; DE 3750545 T 19871230; ES 87119380 T 19871230