

Title (en)

COMMUNICATION ANTENNA WITH A REFLECTOR

Publication

EP 0274693 B1 19920729 (FR)

Application

EP 87118617 A 19871215

Priority

FR 8617758 A 19861218

Abstract (en)

[origin: US4825218A] A telecommunications antenna is provided with a reflector having a semi-offset geometry, a feed mounted on a feed source rigidly fixed to the reflector, an antenna pedestal for supporting the reflector and the feed. Positioning of the feed is such that, in respect of a reflector illumination half-angle beta as seen from the feed such that $45 \text{ DEG} < \beta < 55 \text{ DEG}$, the offset angle alpha (angle between the focal axis DELTA Foc and the median ray of the total beam which is emitted by the feed and illuminates the reflector) is $25 \text{ DEG} < \alpha < 35 \text{ DEG}$, the antenna mount being of the azimuth-elevation type known as an az-el mount.

IPC 1-7

H01Q 1/12; H01Q 3/08; H01Q 19/13

IPC 8 full level

H01Q 1/12 (2006.01); **H01Q 3/08** (2006.01); **H01Q 19/13** (2006.01)

CPC (source: EP US)

H01Q 1/125 (2013.01 - EP US); **H01Q 19/132** (2013.01 - EP US)

Cited by

FR2761817A1

Designated contracting state (EPC)

DE FR GB IT NL SE

DOCDB simple family (publication)

EP 0274693 A1 19880720; EP 0274693 B1 19920729; DE 3780794 D1 19920903; DE 3780794 T2 19930211; FR 2608846 A1 19880624;
FR 2608846 B1 19890324; JP S63172503 A 19880716; US 4825218 A 19890425

DOCDB simple family (application)

EP 87118617 A 19871215; DE 3780794 T 19871215; FR 8617758 A 19861218; JP 32111887 A 19871218; US 3582387 A 19870408