

Title (en)
Milling head.

Title (de)
Messerkopf.

Title (fr)
Tête de fraisage.

Publication
EP 0275073 A2 19880720 (DE)

Application
EP 88100298 A 19880112

Priority
DE 3701053 A 19870116

Abstract (en)
The cutter (4) of the milling head has a guide part (20, 21) which engages into a guide (22, 23; 26, 27) extending in the adjusting direction of the cutter. The cutter (4) bears under spring force against a stop (32, 33) adjustable in the adjusting direction of the cutter and can be adjusted relative to a supporting part (7). For the adjustment of the cutter (4) the stop (32, 33) is adjusted in the adjusting direction of the cutter (4) which is thereby pushed after it under the spring force. The supporting part (7) itself is not adjusted. The readjustment of the cutter (4) is consequently simple and time-saving. <IMAGE>

Abstract (de)
Das Messer (4) des Messerkopfes (1) weist einen Führungsteil (20, 21) auf, der in eine in Verstellrichtung des Messers sich erstreckende Führung (22,23; 26,27) eingreift. Das Messer (4) liegt unter Federkraft (34) an einem in Verstellrichtung des Messers verstellbaren Anschlag (32,33) an und ist gegenüber einem Stützteil (7) verstellbar. Zum Verstellen des Messers (4) wird der Anschlag (32,33) in Verstellrichtung des Messers (4) verstellt, das hierbei unter der Federkraft nachgeschoben wird. Der Stützteil (7) selbst wird nicht verstellt. Dadurch ist die Nachstellung des Messers (4) einfach und zeitsparend.

IPC 1-7
B27G 13/04

IPC 8 full level
B27G 13/04 (2006.01)

CPC (source: EP)
B27G 13/04 (2013.01)

Cited by
EP3623127A1; EP0345570A1; AT216U1; EP3305489A1; CH713020A1; WO9407665A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0275073 A2 19880720; EP 0275073 A3 19891123; EP 0275073 B1 19930407; AT E87853 T1 19930415; DE 3701053 A1 19880728; DE 3879967 D1 19930513

DOCDB simple family (application)
EP 88100298 A 19880112; AT 88100298 T 19880112; DE 3701053 A 19870116; DE 3879967 T 19880112