

Title (en)

CUTTING METHOD AND DEVICE FOR PATTERNED FABRICS

Publication

EP 0275794 B1 19910605 (FR)

Application

EP 87402992 A 19871228

Priority

FR 8618490 A 19861231

Abstract (en)

[origin: US4905159A] A method of cutting out pieces which are to be assembled from a length of check fabric 1 in order to obtain continuity or alignment in the design on the fabric at at least some of the assembly points includes the steps of placing a length of fabric on a cutting-out table 2, storing the shapes, positions, and orientations of the pieces to be cut out in a computer memory, with a margin having a width equal to one half of a design element being reserved around some of the pieces in one or two directions, and also storing the positions of points A, B which are to coincide when the pieces are assembled. A pair of images of the fabric, each centered on a corresponding one of the points, are displayed on a screen 8 side by side, and linear and/or angular offsets between the designs are observed, whereafter any offsets are corrected such that the designs correspond in at least one direction.

IPC 1-7

A41H 43/00; B26F 1/38

IPC 8 full level

B26D 5/00 (2006.01); **A41H 43/00** (2006.01); **B26F 1/38** (2006.01); **D06H 7/00** (2006.01)

CPC (source: EP US)

B26D 5/00 (2013.01 - EP US); **B26D 5/005** (2013.01 - EP US); **B26D 5/007** (2013.01 - EP US); **B26F 1/38** (2013.01 - EP US);
B26D 2005/002 (2013.01 - EP US)

Cited by

FR2659899A1; EP0518473A3; EP0577842A4; FR2702781A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

US 4905159 A 19900227; AT E64065 T1 19910615; BR 8707161 A 19880816; DE 3770614 D1 19910711; EP 0275794 A1 19880727;
EP 0275794 B1 19910605; FR 2608960 A1 19880701; FR 2608960 B1 19891124; JP S63190071 A 19880805

DOCDB simple family (application)

US 13875487 A 19871229; AT 87402992 T 19871228; BR 8707161 A 19871230; DE 3770614 T 19871228; EP 87402992 A 19871228;
FR 8618490 A 19861231; JP 33680687 A 19871229