

## Title (en)

Feeding device for adhesive strips in binding machines for continuous form sets.

## Title (de)

Zuführvorrichtung für Klebstoffstreifen in Maschinen zum Verbinden von Endlosformularsätzen.

## Title (fr)

Dispositif d'alimentation des points de ruban collé pour relieuse d'imprimés en liasse continus de tabulatrice.

## Publication

**EP 0276199 A2 19880727 (FR)**

## Application

**EP 88830025 A 19880121**

## Priority

IT 930687 A 19870122

## Abstract (en)

The feed mechanism is for the glued points on a ribbon in a machine binding continuous bundles of tabulator print-outs, having a toothed ring (4) inserting the front part of each point (3) in a hole in the bundle margin (5), while a pair of rollers (6,6') feed the continuous bundles forward and secure the front part below the bottom printed sheet. A pair of rollers (14,14') on horizontal axes one above the other and parallel to the direction of movement of the sheets index the glued ribbon (16) forward from a storage roll (18), being driven by a ratchet mechanism (33,34,35) with cam (30). A head (21) rotates in a vertical plane above the margin holes, and has an eccentric knife (28) and a concentric surface (28') parting off the ribbon and retracting part of the binding. This works opposite a rubber-covered roller (39) lifting the sheets and is rotated in synchronism with movement of the latter and with the ribbon. The roller is also lifted in synchronism with rotation of the head.

## Abstract (fr)

Dispositif d'alimentation des points de ruban collé pour relieuse d'imprimés en liasse continus de tabulatrices avec une couronne dentée (4), pour insérer la partie antérieure de chaque point dans un trou correspondant de la perforation prévue sur les bords des imprimés en liasse (5) superposés en phase de reliure et une paire de rouleaux (6) pour entraîner lesdits imprimés en liasse (5) et fixer ladite partie antérieure de chaque point sous l'imprimé inférieur, caractérisé en ce qu' il comprend une paire de rouleaux (14,15) pour entraîner le ruban collé (16) dans une direction perpendiculaire à celle de déplacement des imprimés en liasse, et avec déplacement par intermittence obtenu au moyen d'un système à cliquet (32,33,34) associé à une came (30) cosmodronique; une tête (21) tournant verticalement dans le sens de déplacement des imprimés en liasse et qui est pourvue d'au-moins un taillant (28) excentrique et d'un presseur correspondant (28') pour effectuer, à chaque tour, le découpage du ruban collé (16) en retirant un point de reliure (3) et ainsi pour fixer, en coopération avec un rouleau caoutchouté (39) en opposition qui soulève les imprimés en liasse (5), la partie postérieure dudit point sur l'imprimé supérieur; des moyens pour obtenir la rotation de la tête (21) en synchronisme avec le déplacement des imprimés en liasse (5) à relier et des moyens pour obtenir le déplacement du ruban collé (16) en synchronisme avec la rotation de la tête (21).

## IPC 1-7

**B42C 3/00**; **B65H 37/04**

## IPC 8 full level

**B42C 3/00** (2006.01); **B65H 37/04** (2006.01)

## CPC (source: EP US)

**B42C 3/00** (2013.01 - EP US); **B65H 37/04** (2013.01 - EP US); **B65H 2301/43151** (2013.01 - EP US); **Y10T 156/1322** (2015.01 - EP US); **Y10T 156/133** (2015.01 - EP US); **Y10T 156/1343** (2015.01 - EP US)

## Designated contracting state (EPC)

AT BE CH DE ES FR GB GR LI LU NL SE

## DOCDB simple family (publication)

**EP 0276199 A2 19880727**; **EP 0276199 A3 19900307**; **EP 0276199 B1 19920617**; AT E77308 T1 19920715; DE 3871963 D1 19920723; DE 3871963 T2 19930107; ES 2034373 T3 19930401; GR 3005627 T3 19930607; IT 1207824 B 19890601; IT 8709306 A0 19870122; US 4959046 A 19900925

## DOCDB simple family (application)

**EP 88830025 A 19880121**; AT 88830025 T 19880121; DE 3871963 T 19880121; ES 88830025 T 19880121; GR 920401955 T 19920907; IT 930687 A 19870122; US 21142988 A 19880624