

Title (en)
FLUSHING CISTERN

Publication
EP 0276633 A3 19881214 (DE)

Application
EP 87810749 A 19871214

Priority
CH 25787 A 19870126

Abstract (en)
[origin: EP0276633A2] Inserted into the flushing cistern is a holder (1), to which the inlet valve (3) and an angle lever (2) for actuating the outlet valve (13) are fastened. The valve (3) and the angle lever (2) can be fastened removably by preassembly to a fastening element (19) and to a pedestal (7). In a built-in flushing cistern, for final mounting, the holder (1) together with the parts fastened to it is inserted into the flushing cistern through the inspection orifice. <IMAGE>

IPC 1-7
E03D 5/092

IPC 8 full level
E03D 1/012 (2006.01); **E03D 5/092** (2006.01)

CPC (source: EP)
E03D 1/012 (2013.01); **E03D 5/092** (2013.01)

Citation (search report)

- [X] US 2357213 A 19440829 - MAIGE GEORGE D
- [A] AU 420994 B2 19720201
- [AD] CH 651341 A5 19850913 - GEBERIT AG

Cited by
EP0893543A1; EP0893542A1; EP0694656A1; WO9954561A1; DE102017116520A1; EP0964105A3; DE19508865A1; DE19508865C2; EP0964105A2

Designated contracting state (EPC)
AT BE FR IT NL

DOCDB simple family (publication)
EP 0276633 A2 19880803; EP 0276633 A3 19881214; EP 0276633 B1 19910904; EP 0276633 B2 19950426; AT E66991 T1 19910915; CH 673860 A5 19900412; DE 3710097 A1 19880804; DE 3710097 C2 19950518; DE 3710097 C3 20001026; DK 26288 A 19880727; DK 26288 D0 19880121

DOCDB simple family (application)
EP 87810749 A 19871214; AT 87810749 T 19871214; CH 25787 A 19870126; DE 3710097 A 19870327; DK 26288 A 19880121