

Title (en)
TELLER DOOR

Publication
EP 0276650 B1 19911016 (DE)

Application
EP 88100039 A 19880105

Priority
CH 19187 A 19870120

Abstract (en)
[origin: EP0276650A1] In order, on the one hand, to protect the teller against attacks and, on the other hand, to allow small and large articles to be passed across the counter, the counter door has a frame (1) limiting the counter aperture (2). With the door closed, a first rectangular plate (7) closes off the lower part of the counter aperture (2), whilst the upper part is closed off by a second rectangular plate (8). The plates (7, 8) are mounted vertically displaceably on the frame (1). The first plate (7) is displaceable, by a drive arranged in the frame and with self-locking, with its lower longitudinal edge as far as the upper limitation (5) of the counter aperture (2) and back again. The second plate (8) is suspended laterally by means of a respective deflecting roller in a rope loop (24), which rope loops are fastened with one leg to the frame (1) and with the other leg to the first plate (7). There are means which prevent the second plate (7) from being lifted off from the rope loops. <IMAGE>

IPC 1-7
E05G 7/00

IPC 8 full level
E05G 7/00 (2006.01)

CPC (source: EP)
E05G 7/004 (2013.01)

Cited by
GB2336385A; US5860371A; DE19525946A1; US5636579A; GB2338978A; GB2338978B; DE102015012570A1; GB2268957A; GB2268957B; GB2341200A; GB2341200B; GB2338979A; GB2338979B; GB2343213A; GB2343213B; EP0716209A1; NL9402109A; DE102015012570B4

Designated contracting state (EPC)
AT BE DE ES FR GB GR IT LU NL SE

DOCDB simple family (publication)
EP 0276650 A1 19880803; EP 0276650 B1 19911016; AT E68553 T1 19911115; CH 671604 A5 19890915; DE 3865441 D1 19911121

DOCDB simple family (application)
EP 88100039 A 19880105; AT 88100039 T 19880105; CH 19187 A 19870120; DE 3865441 T 19880105