

Title (en)
PILE DRIVER

Publication
EP 0276845 B1 19920722 (EN)

Application
EP 88101219 A 19880128

Priority
JP 2012887 A 19870130

Abstract (en)
[origin: EP0276845A2] The present invention provides a pile driver comprising a vibration cylinder (3) and a self-equilibration cylinder (7) so provided vertically in series with each other that the axes of their respective rods lie on the center line passing through the center of gravity of an inertial weight (1), the rods of the vibration and self-equilibration cylinders being coupled to each other, the vibration cylinder having provided therein a changeover valve (10) to supply and discharge a pressurized fluid to and from the vibration cylinder, the self-equilibration cylinder having provided therein a control valve (11) responsive to the rod of either the self-equilibration cylinder or vibration cylinder to supply and discharge the pressurized fluid to and from a control chamber in the self-equilibration cylinder. The piston of the self-equilibration cylinder is supported with a low rigidity to the inertial weight by means of accumulators (14) provided as communicating with the control chambers in the self-equilibration cylinder, and also the self-equilibration cylinder or vibration cylinder has provided at the lower end of the rod thereof a chuck (17) which grasps the pile.

IPC 1-7
E02D 7/18

IPC 8 full level
E02D 7/18 (2006.01); **E02D 13/10** (2006.01)

CPC (source: EP)
E02D 7/18 (2013.01); **E02D 13/10** (2013.01)

Cited by
KR100494072B1; EP0449286A1; US9938983B2

Designated contracting state (EPC)
CH DE FR GB IT LI NL

DOCDB simple family (publication)
EP 0276845 A2 19880803; EP 0276845 A3 19891018; EP 0276845 B1 19920722; DE 3872889 D1 19920827; DE 3872889 T2 19930304; JP S63189522 A 19880805

DOCDB simple family (application)
EP 88101219 A 19880128; DE 3872889 T 19880128; JP 2012887 A 19870130