

Title (en)
DEVICE FOR SYNTHESIZING IMAGES

Publication
EP 0276884 B1 19920415 (FR)

Application
EP 88200089 A 19880120

Priority
FR 8700917 A 19870127

Abstract (en)
[origin: US4866524A] In a system in which there are available several pictures the device according to the invention enables the management of the overlays of pictures by implementing a mechanism according to which transition points are defined during the scanning. At these transition points, the mode of display changes. The horizontal position of these points and the nature of the display change are contained in a special register (13). An abscissa comparator (12) continuously compares the current abscissa and the abscissa indicated in the register (13) and, after an abscissa identity has been found and a new overlay mode has been set up, the next word in the register (13) is taken into account. Means (5, 8) enable the content of the register (13) to be reloaded during the line scan return periods.

IPC 1-7
G09G 1/00; G09G 1/16

IPC 8 full level
G09G 5/00 (2006.01); **G09G 5/06** (2006.01); **G09G 5/14** (2006.01); **G09G 5/32** (2006.01); **G09G 5/36** (2006.01); **G09G 5/395** (2006.01)

CPC (source: EP KR US)
G09G 1/00 (2013.01 - KR); **G09G 5/14** (2013.01 - EP US); **G09G 5/395** (2013.01 - EP US)

Cited by
EP0840276A3; EP0669019A4; EP0840277A3; US6310657B1; US6452641B1

Designated contracting state (EPC)
BE DE FR GB IT NL

DOCDB simple family (publication)
EP 0276884 A1 19880803; EP 0276884 B1 19920415; DE 3869974 D1 19920521; FR 2610160 A1 19880729; FR 2610160 B1 19890324; JP S63193177 A 19880810; KR 880009518 A 19880915; KR 970000824 B1 19970120; US 4866524 A 19890912

DOCDB simple family (application)
EP 88200089 A 19880120; DE 3869974 T 19880120; FR 8700917 A 19870127; JP 1476888 A 19880127; KR 880000611 A 19880127; US 14652788 A 19880121