

Title (en)

RAIL VEHICLE HAVING ITS LOAD DISTRIBUTED AMONG THE FOUR AXLES WHICH ARE ROTATABLE RELATIVE TO THE SUPERSTRUCTURE

Publication

**EP 0277059 B1 19910828 (FR)**

Application

**EP 88400078 A 19880115**

Priority

FR 8700479 A 19870116

Abstract (en)

[origin: US4986191A] The invention relates to a railway vehicle comprising two sets of two axles which are steerable relative to the body. The load of the body is applied in the vertical plane of each axle at two points adjacent to the wheels. The load of the body is applied through slide friction blocks. The invention concerns in particular railway vehicles wherein each axle is radially guided.

IPC 1-7

**B61F 5/14**; **B61F 5/44**

IPC 8 full level

**B61F 5/14** (2006.01); **B61F 5/18** (2006.01); **B61F 5/44** (2006.01)

CPC (source: EP US)

**B61F 5/44** (2013.01 - EP US)

Cited by

WO2009071768A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0277059 A1 19880803**; **EP 0277059 B1 19910828**; AT E66650 T1 19910915; CA 1311966 C 19921229; DE 3864409 D1 19911002; ES 2025296 B3 19920316; FR 2609677 A1 19880722; FR 2609677 B1 19911227; GR 3002709 T3 19930125; JP H078647 B2 19950201; JP S63279967 A 19881117; US 4986191 A 19910122; ZA 88301 B 19880928

DOCDB simple family (application)

**EP 88400078 A 19880115**; AT 88400078 T 19880115; CA 556669 A 19880115; DE 3864409 T 19880115; ES 88400078 T 19880115; FR 8700479 A 19870116; GR 910401311 T 19910912; JP 670988 A 19880114; US 40901389 A 19890918; ZA 88301 A 19880118