

Title (en)  
ROOFING FRAME FOR ROOF LIGHTS, DOORS OR THE LIKE

Publication  
**EP 0277497 A3 19880921 (DE)**

Application  
**EP 88100353 A 19880113**

Priority  
DE 8701605 U 19870203

Abstract (en)  
[origin: EP0277497A2] To obtain a waterproof transition between the roofing frame of a rooflight and the roof, lead aprons are used. For this, the material is unwound downwards from relatively large rolls, starting from the frame, and is then stretched in order to match it to the shape of the roof tiles. For this purpose, the material is pressed clean into the recess of the tiles by means of a fold, and often cracks, through which water can penetrate, occur in the lead apron. Since the lead apron is exposed directly to the weather, the lead disintegrates over the years, and therefore a greater thickness than is actually necessary has to be chosen at the outset. In addition, a disintegrated lead apron has an unpleasant appearance and is seen as a foreign body on the roof. The new roofing frame for windows, doors or the like is to be designed in such a way that the danger of cracks in the lead apron is reduced and a permanent decorative appearance becomes possible, whilst at the same time preventing lead secretions as a result of weathering. A further object is to prevent harmful lead secretions as a result of weathering and consequently to improve environmental protection in roof coverings, facades and auxiliary materials for sealing transitions in roof, wall and corner connections. The roofing frame of rooflights, doors or the like consists of a ridge, a breastplate, two flashings and a lead apron which is covered with at least one aluminium layer. Roofing frames of rooflights, doors or the like and lead strips of any kind for roof coverings, facade claddings or auxiliary materials for roofs and walls. <IMAGE>

IPC 1-7  
**E04D 13/14**

IPC 8 full level  
**E04D 13/14** (2006.01); **E04D 13/147** (2006.01)

CPC (source: EP)  
**E04D 13/1475** (2013.01)

Citation (search report)  
• [Y] DE 2263565 A1 19740704 - MARZARI SIEGFRIED  
• [Y] EP 0038222 A2 19811021 - RASMUSSEN HOLDING AS V KANN [DK]  
• [A] GB 1602718 A 19811118 - ROSS A B G, et al  
• [A] DE 1609922 A1 19700416 - BRIEL KARL WILHELM  
• [A] FR 2333913 A1 19770701 - BRAAS & CO GMBH [DE]  
• [A] CAHIERS DU CENTRE SCIENTIFIQUE ET TECHNIQUE DU BATIMENT, Nr. 244, November 1983, Seiten 1-8, "avis technique", Nr. 5/83-442; Paris, FR: "Avis sur les closoirs aérés de faîtage et d'arêtier VM 770 et les raccords sur mur frontal"

Cited by  
DE19833256C2; AT143U1; DE3832070C5; DE3845023B4; EP0389058A1; EP2077302A1; US11592197B2; WO2004042164A1; WO9509287A1

Designated contracting state (EPC)  
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0277497 A2 19880810; EP 0277497 A3 19880921; EP 0277497 B1 19910515**; AT E63594 T1 19910615; DE 3862761 D1 19910620; DE 8701605 U1 19870507; ES 2023223 B3 19920101; GR 3002387 T3 19921230

DOCDB simple family (application)  
**EP 88100353 A 19880113**; AT 88100353 T 19880113; DE 3862761 T 19880113; DE 8701605 U 19870203; ES 88100353 T 19880113; GR 910400624 T 19910726