

Title (en)  
APPARATUS FOR MOUNTING A REEL CORE ON A PRINTING CYLINDER

Publication  
**EP 0277545 B1 19901212 (DE)**

Application  
**EP 88100781 A 19880120**

Priority  
DE 3702889 A 19870131

Abstract (en)  
[origin: US4823693A] To prevent shifting of an eccentric (12, 33) about a bearing (8, 26), which it surrounds to provide for adjustable positioning of a printing cylinder (3) in a printing machine, upon release of the eccentric from a sidewall (1) of a printing machine to permit placing a sleeve (15) over the cylinder, the eccentric, in accordance with the invention, is locked in position to the shaft of the cylinder, or to the sidewall, or a releasable jaw of the machine prior to release of the eccentric from clamp holding position between holding jaws (13, 27, 28) which, in operation, retain the eccentric in position on the machine.

IPC 1-7  
**B41F 27/06; B41F 30/04**

IPC 8 full level  
**B41F 13/00** (2006.01); **B41F 13/20** (2006.01); **B41F 13/36** (2006.01); **B41F 27/06** (2006.01); **B41F 27/10** (2006.01); **B41F 30/04** (2006.01)

CPC (source: EP US)  
**B41F 13/20** (2013.01 - EP US); **B41F 13/36** (2013.01 - EP US); **B41F 27/105** (2013.01 - EP US); **B41F 30/04** (2013.01 - EP US);  
**B41P 2227/21** (2013.01 - EP US); **Y10T 29/49863** (2015.01 - EP US)

Cited by  
EP1721742A3; EP1010522A1; DE3943746C2; EP3144145A4; EP0659554A3; EP0657283A1; NL9302062A; EP0406694A3; DE10102269A1; DE10102269B4; DE4332364A1; EP0596244A1; DE4341246C1; FR2713142A1; EP0421145A3; EP0663291A1; US5524539A; EP0683041A1; US5692439A; DE4415340A1; EP1327523A1; US7543531B2; US10850499B2; EP0683043A1; WO2006013046A1; WO2005014287A1; US10737482B2; US10857780B2; US11331903B2

Designated contracting state (EPC)  
CH DE FR GB IT LI SE

DOCDB simple family (publication)  
**EP 0277545 A2 19880810; EP 0277545 A3 19881117; EP 0277545 B1 19901212**; CA 1316043 C 19930413; DE 3702889 A1 19880811; DE 3861244 D1 19910124; JP 2726050 B2 19980311; JP S63193841 A 19880811; US 4823693 A 19890425

DOCDB simple family (application)  
**EP 88100781 A 19880120**; CA 558227 A 19880205; DE 3702889 A 19870131; DE 3861244 T 19880120; JP 1972488 A 19880201; US 15008988 A 19880129