

Title (en)  
HINGE JOINT AND ITS USE

Publication  
**EP 0278266 B1 19901212 (DE)**

Application  
**EP 88100714 A 19880120**

Priority  
CH 43487 A 19870206

Abstract (en)  
[origin: EP0278266A1] The hinge joint has a joint head (5) to be arranged on the tilting bar (4) and a connecting part, which forms the joint socket, to be arranged on the slat (1). To simplify the assembly of the roller blind, it is envisaged that the connecting part has an elongate plate (8) to be arranged parallel on the slat flange, from which plate two locking pins (12), which are at a distance from one another in the longitudinal direction of the plate (8), project out to one side. Their locking hooks (11) face towards one another. Two cheeks (14) project out from the opposite side of the plate, which in relation to the longitudinal direction of the plate lie between the locking pins (12) and form the joint socket. <IMAGE>

IPC 1-7  
**E06B 9/384**

IPC 8 full level  
**E06B 9/384** (2006.01)

CPC (source: EP)  
**E06B 9/384** (2013.01)

Cited by  
CH711490A1; EP0777031A1; CH707481A1; DE4011747A1; AT401084B; DE4011747C2

Designated contracting state (EPC)  
AT BE DE ES FR GB GR IT LU NL SE

DOCDB simple family (publication)  
**EP 0278266 A1 19880817; EP 0278266 B1 19901212**; AT E59084 T1 19901215; CH 672813 A5 19891229; DE 3861246 D1 19910124

DOCDB simple family (application)  
**EP 88100714 A 19880120**; AT 88100714 T 19880120; CH 43487 A 19870206; DE 3861246 T 19880120