

Title (en)

Device for collating folded printed sheets.

Title (de)

Einrichtung zum Sammeln von gefalteten Druckbogen.

Title (fr)

Dispositif pour assembler des feuilles imprimées pliées.

Publication

**EP 0278286 A2 19880817 (DE)**

Application

**EP 88100908 A 19880122**

Priority

CH 51087 A 19870211

Abstract (en)

[origin: JPS6434850A] PURPOSE: To completely align edges adjacent to printed signatures or sheets mutually by disposing a stop element for pushing the printed signatures or sheets to a sliding pusher dog in the transfer range of each infeed conveyor. CONSTITUTION: In a second overlapping conveyor 18, a printed signature or sheet 30 is dropped on an already existing printed signature or sheet 28 by a distance (d) in front, and fed in the direction of an arrow 34 while the distance (d) is maintained. Then, the overlapping conveyor 18 is sent from left to right, the printed signature or sheet 30 on a fourth overlapping conveyor 18 is protruded into contact with a stop element 36 and, while the printed signature or sheet 28 therebelow is continuously fed, further feeding motion caused by friction connection is prevented by the stop element 36. Then, when a pusher dog 33 approaches the stop element 36 by spacing coincident with the dimensions of the printed signatures or sheets 28 and 30, the printed signatures or sheets 28 and 30 are completely aligned, and simultaneously passed through the tail end of the stop element 36.

Abstract (de)

Durch Zuförderer (22, 23, 24) werden Druckbogen (28, 30, 31) einzeln rittlings auf mit schiebenden Mitnehmern (33) versehene Sammelförderer (18) aufgelegt. Es sind mehrere, parallel zueinander verlaufende, in gleichmässigen Umfangsabständen voneinander um eine Umlaufachse (14) angeordnete und um diese umlaufende Sammelförderer (18) vorgesehenen. Um schon während des Sammelns der Druckbogen eine deckungsgleiche Ausrichtung deren Kanten zu erreichen, sind im Bereich der Uebergabestelle jedes der Zuförderer (22, 23, 24) Anschlagelemente (35, 36, 37) angeordnet, um die Druckbogen (28, 30, 31) jeweils gegen den schiebendenen Mitnehmer (33) zu drängen.

IPC 1-7

**B42B 9/04; B65H 5/32; B65H 9/10; B65H 39/06; B65H 39/065**

IPC 8 full level

**B65H 29/40** (2006.01); **B42B 9/04** (2006.01); **B65H 5/16** (2006.01); **B65H 5/32** (2006.01); **B65H 9/10** (2006.01); **B65H 31/28** (2006.01);  
**B65H 39/065** (2006.01)

CPC (source: EP US)

**B42B 9/04** (2013.01 - EP US); **B65H 5/32** (2013.01 - EP US); **B65H 9/101** (2013.01 - EP US); **B65H 39/065** (2013.01 - EP US);  
**B65H 2301/436** (2013.01 - EP US); **B65H 2301/4361** (2013.01 - EP US); **B65H 2301/44795** (2013.01 - EP US)

Cited by

CH687459A5; DE19511777B4

Designated contracting state (EPC)

CH DE GB LI SE

DOCDB simple family (publication)

**EP 0278286 A2 19880817; EP 0278286 A3 19900516; EP 0278286 B1 19930811;** DE 3883019 D1 19930916; FI 880616 A0 19880210;  
FI 880616 A 19880812; FI 91382 B 19940315; FI 91382 C 19940627; JP 2525633 B2 19960821; JP S6434850 A 19890206;  
US 4811938 A 19890314

DOCDB simple family (application)

**EP 88100908 A 19880122;** DE 3883019 T 19880122; FI 880616 A 19880210; JP 2555088 A 19880205; US 15358488 A 19880208