

Title (en)

SEWING MACHINE FOR SEWING A RUBBER STRIP

Publication

**EP 0278967 B1 19910529 (DE)**

Application

**EP 87905611 A 19870825**

Priority

DE 3628829 A 19860825

Abstract (en)

[origin: WO8801660A2] Sewing machine for sewing a rubber strip to a tubular end-piece of a garment made from an elastic textile material in order to produce an endless elastic band. The sewing machine comprises a sewing foot (18) with an insertion opening (22) for the elastic band (24), a braking device (48) to resist the insertion movement of the elastic band and provided with two clamping elements (50, 52) which grip the band, and a cutting system (26) which can be motor-driven, in order to cut the rubber band. In order to prevent, after said cutting, the reintroduction of band (24) into the insertion opening (22) of the sewing foot (18), the cutting system (26) is arranged behind the insertion aperture (22) of the sewing foot (18) on the latter, and a drive system (56) is associated with the braking device (48) in order to increase the gap between the two clamping elements (50, 52) immediately before actuation of the cutting system (26).

IPC 1-7

**D05B 35/06**

IPC 8 full level

**D05B 35/06** (2006.01); **D05B 29/06** (2006.01)

CPC (source: EP US)

**D05B 35/06** (2013.01 - EP US); **D05B 29/06** (2013.01 - EP US); **D05D 2207/02** (2013.01 - EP US); **D05D 2207/04** (2013.01 - EP US);  
**D05D 2303/04** (2013.01 - EP US); **D05D 2305/04** (2013.01 - EP US); **D05D 2305/12** (2013.01 - EP US)

Designated contracting state (EPC)

CH FR GB IT LI

DOCDB simple family (publication)

**DE 3628829 C1 19880211**; EP 0278967 A1 19880824; EP 0278967 B1 19910529; JP H01500644 A 19890309; US 4909165 A 19900320;  
WO 8801660 A2 19880310

DOCDB simple family (application)

**DE 3628829 A 19860825**; EP 8700480 W 19870825; EP 87905611 A 19870825; JP 50514587 A 19870825; US 19499488 A 19880531