

Title (en)
WEATHERSTRIPPING E.G. FOR AUTOMOBILES

Publication
EP 0279100 B1 19910327 (EN)

Application
EP 87306980 A 19870806

Priority
US 754387 A 19870128

Abstract (en)
[origin: EP0279100A1] A resilient weatherstrip for an automobile door has a hollow, mushroom-shaped bulbous portion (7) which is integral with a metal reinforced carrier (8) that attaches to the flange (9) of the automobile frame surrounding the door. The carrier has fingers (26,27) with stops (28,29) for engaging abutments (32,33) which project into the opening through which the flange (9) passes as the carrier (8) is mounted in the door opening. The flange (9) pushes the fingers (26,27) apart so that the stops (28,29) interlock with the abutments should the carrier attempt to leave the flange. The bulbous portion (7) has a cap portion (12) carried by stem portions (13,14). The wall thickness of the stem portions (13,14) increases towards the carrier (8), and the wall thickness of the cap portion (12) increases towards its peak (16). This shape gives the bulbous portion good characteristics when compressed.

IPC 1-7
B60R 13/06

IPC 8 full level
B60R 13/06 (2006.01); **B60J 10/00** (2006.01); **B60J 10/08** (2006.01); **E06B 7/23** (2006.01)

CPC (source: EP US)
B60J 10/16 (2016.02 - EP US); **B60J 10/242** (2016.02 - EP US); **B60J 10/33** (2016.02 - EP US); **B60J 10/80** (2016.02 - EP US); **E06B 7/2309** (2013.01 - EP US); **E06B 7/2314** (2013.01 - EP US); **Y10T 24/44855** (2015.01 - EP US)

Cited by
FR2863211A1; EP1293372A1; DE19856733A1; DE19856733B4; GB2272470A; EP0397300A3; US6889472B2

Designated contracting state (EPC)
BE DE ES FR IT LU NL

DOCDB simple family (publication)
US 4702039 A 19871027; CA 1284162 C 19910514; DE 3768939 D1 19910502; EP 0279100 A1 19880824; EP 0279100 B1 19910327; ES 2021718 B3 19911116; JP S63188543 A 19880804

DOCDB simple family (application)
US 754387 A 19870128; CA 544834 A 19870819; DE 3768939 T 19870806; EP 87306980 A 19870806; ES 87306980 T 19870806; JP 20299687 A 19870813