

Title (en)
DEEP FRYER FOR DOMESTIC USE

Publication
EP 0279262 B1 19900801 (FR)

Application
EP 88101380 A 19880201

Priority
FR 8701554 A 19870209

Abstract (en)
[origin: EP0279262A1] 1. A domestic frying device comprising, in a casing (10), a bowl (12) containing a cooking bath constituted either by oil or by fat derived from melting a block of fat, an electric heating resistor (14) adapted to heat the cooking bath, a thermostatic control switch (38) mounted in series with the heating resistor (14) and a basket (16) to hold the foods to be fried which is movably mounted in the basket and can occupy, thanks to electromechanical means (20) for lowering and raising the basket, the supply of electricity to which is under the control of a control device, either a lowered position in which the basket is immersed in the bath or a raised position in which the basket is held above the bath ; the control device comprises a safety switch (62) which is mounted in series in the supply circuit of the electromechanical means (20) and the operation of which is controlled by a sensor adapted to detect a pre-determined state of the cooking bath in such a way that the said switch (62) may occupy either a conducting state in which it closes the said supply circuit and permits the actuation of the electromechanical means (20) by the control device, and into which it is brought after the sensor detects the said pre-determined state, or a non-conducting state in which it opens the supply circuit and thus prevents the actuation of the electromechanical means (20) by the said control device, characterized in that the pre-determined state of the cooking bath which the sensor is adapted to detect corresponds to the almost complete melting of a block of fat and in that the control device also comprises a manually controlled selector switch (66) which is mounted in parallel to the terminals (63 and 65) of the safety switch (62) and the movable armature (68) of which may occupy either an "oil" position, in which the said switch (62) is short-circuited, or a "fat" position in which this switch (62) performs its function as an electrical safety switch in the supply circuit of the electromechanical means (20) for raising and lowering the basket.

IPC 1-7
A47J 37/12

IPC 8 full level
A47J 37/12 (2006.01)

CPC (source: EP)
A47J 37/1219 (2013.01)

Cited by
EP0350340A1; FR2633818A1; WO2019213087A1

Designated contracting state (EPC)
AT BE CH DE ES GB GR IT LI NL SE

DOCDB simple family (publication)
EP 0279262 A1 19880824; EP 0279262 B1 19900801; AT E55047 T1 19900815; DE 3860372 D1 19900906; ES 2016663 B3 19901116; FR 2610503 A1 19880812; FR 2610503 B1 19910614; GR 3000955 T3 19911210; PT 86720 A 19890228; PT 86720 B 19930831

DOCDB simple family (application)
EP 88101380 A 19880201; AT 88101380 T 19880201; DE 3860372 T 19880201; ES 88101380 T 19880201; FR 8701554 A 19870209; GR 900400633 T 19901019; PT 8672088 A 19880208