

Title (en)
ELECTRICAL CONNECTOR

Publication
EP 0280450 B1 19930407 (EN)

Application
EP 88301246 A 19880215

Priority
JP 2803687 U 19870226

Abstract (en)
[origin: EP0280450A2] A bottom-entry circuit board mounted female connector (1) has an integrally molded dielectric housing (2) having a board engaging surface on bottom wall (11) and a plurality of terminal receiving cavities (7). A plurality of spring contact female terminals (8) are mounted one in each cavity (7). A plurality of inlet openings (13), for male terminals (24) (see Figs. 8 and 9) are defined in the wall (11). Barrier means in the form of an integral unitary flap member (14) hingeably connected to one side of each inlet opening (13) is provided to prevent wicking invasion of flux into the cavities (7) and electrical contact areas during flux treatment preparatory to wave soldering.

IPC 1-7
H01R 13/453; H01R 23/72

IPC 8 full level
H01R 4/02 (2006.01); **H01R 13/453** (2006.01); **H01R 24/00** (2006.01)

CPC (source: EP)
H01R 4/028 (2013.01); **H01R 12/716** (2013.01); **H01R 13/4536** (2013.01)

Cited by
FR2866484A1; US5626482A; DE10204842B4; EP0486845A3; EP0999612A3; US6089904A; SG83104A1; EP3200288A1; CN107026347A; US6655997B2; US6298255B1; US7306494B2; WO0078213A3; WO2005013430A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0280450 A2 19880831; EP 0280450 A3 19891018; EP 0280450 B1 19930407; BR 8800745 A 19881004; DE 3879986 D1 19930513; DE 3879986 T2 19931111; JP H046134 Y2 19920220; JP S63137480 U 19880909

DOCDB simple family (application)
EP 88301246 A 19880215; BR 8800745 A 19880223; DE 3879986 T 19880215; JP 2803687 U 19870226