

Title (en)
IMAGE FORMING APPARATUS AND CONTROL SYSTEM THEREFOR

Publication
EP 0281055 A3 19900606 (EN)

Application
EP 88103008 A 19880229

Priority
JP 4699587 A 19870302

Abstract (en)
[origin: EP0281055A2] A control system for a color copier which sets up an adequate color copying time for any particular size of paper sheets. A color document is repeatedly scanned by scanning optics (58) to sequentially expose a single photoconductive drum (52), which is rotated at a constant speed, to a plurality of separated color components. Each of the latent images electrostatically formed on the drum is developed by toner which is supplied from a developing device and complementary in color to the color component associated with the latent image, the resulting toner images being sequentially transferred to a paper sheet which is held on and rotated together with a transfer drum (66). The control system includes a paper size setting circuit (44) for setting the size of a paper sheet to be used before a copying operation, a scanning sensor (86) for sensing the start of a scanning performed by the optics, and a home sensor (88) for sensing an instantaneous angular position of the transfer drum. A control circuit (98) is constructed to determine a transfer start and a transfer end time in response to a paper size signal outputted by the paper size setting circuit (94), an output signal of the scanning sensor (86), and an output signal of the home sensor (88), and to variably control the rotation speed of the transfer drum during the interval between the transfer start and transfer end times so as to register the leading end of a paper sheet loaded on the transfer drum and that of each of the toner images formed on the photoconductive drum and different in color from each other. The circumferential length of one of the photoconductive and transfer drums is greater than that of the other by a multiple other than integral multiples.

IPC 1-7
G03G 15/01; G03G 15/00

IPC 8 full level
G03G 15/00 (2006.01); **G03G 15/01** (2006.01); **G03G 15/16** (2006.01)

CPC (source: EP)
G03G 15/0131 (2013.01); **G03G 15/1655** (2013.01); **G03G 15/50** (2013.01); **G03G 2215/0196** (2013.01)

Citation (search report)
• [E] US 4733269 A 19880322 - KASAHARA NOBUO [JP], et al
• [E] US 4766463 A 19880823 - WATANUKI MASAYOSHI [JP], et al
• [XP] DE 3704583 A1 19870827 - RICOH KK [JP]
• [XP] US 4705386 A 19871110 - OGITA AKIRA [JP], et al
• [A] US 4260241 A 19810407 - HONMA TOSHIO, et al
• [XD] PATENT ABSTRACTS OF JAPAN, vol. 10, no. 84 (P-442)(2141), 3 April 1986; & JP-A-60 218 673 (FUJI XEROX) 01.11.1985
• [A] PATENT ABSTRACTS OF JAPAN, vol. 9, no. 105 (P-354)(1828), 9 May 1985; & JP-A-59 228 266 (FUJI XEROX) 21.12.1984

Cited by
US5043761A; EP0603819A1; US5539507A; EP0577490A1; US5446528A; US5623333A; EP0523870A3; US5287160A; DE3928729A1; FR2636444A1; US5010372A; US6505015B1; WO9114209A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0281055 A2 19880907; **EP 0281055 A3 19900606**; **EP 0281055 B1 19930811**; DE 3883024 D1 19930916; DE 3883024 T2 19931125; JP S63212961 A 19880905

DOCDB simple family (application)
EP 88103008 A 19880229; DE 3883024 T 19880229; JP 4699587 A 19870302