

Title (en)

LACQUERING PRETREATMENT PROCESS FOR ALUMINIUM OR ALUMINIUM ALLOY WORK PIECES

Publication

EP 0281176 B1 19910925 (DE)

Application

EP 88200205 A 19880205

Priority

DE 3705633 A 19870221

Abstract (en)

[origin: EP0281176A1] In a process for preparing workpieces, which have at least partially been machined with metal removal and have surfaces of aluminium and alloys thereof, for subsequent painting, the workpieces are first treated by annealing and/or pickling in an oxidising acidic medium and then coated with a conversion layer. It is particularly advantageous first to pickle the workpieces in a solution containing HNO₃+HF and/or HNO₃ and subsequently to coat them with a conversion layer by yellow chromation or fluoride-activated zinc manganese phosphating and then to coat them by the electro-dipping process, powder-coating process or high-solids coating process. The process is preferably applicable to the treatment of workpieces having surfaces of alloys of the type AlMg or AlMgMn or of the heat-hardenable type AlMgSi.

IPC 1-7

C23C 22/78; **C23G 1/12**

IPC 8 full level

C23C 22/78 (2006.01); **C23G 1/12** (2006.01)

CPC (source: EP)

C23C 22/78 (2013.01); **C23G 1/125** (2013.01)

Cited by

DE4131382A1; EP2031096A3; EP0557531A4; EP1930474A4; WO0068466A1

Designated contracting state (EPC)

BE DE ES FR IT NL SE

DOCDB simple family (publication)

EP 0281176 A1 19880907; **EP 0281176 B1 19910925**; BR 8800681 A 19881004; DE 3705633 A1 19880901; DE 3865045 D1 19911031; ES 2025763 T3 19920401

DOCDB simple family (application)

EP 88200205 A 19880205; BR 8800681 A 19880219; DE 3705633 A 19870221; DE 3865045 T 19880205; ES 88200205 T 19880205