

Title (en)

CABLEWAY INSTALLATION WITH A DEFLECTED CABLE RUN

Publication

EP 0281205 B1 19911113 (DE)

Application

EP 88200391 A 19880302

Priority

IT 480687 A 19870306

Abstract (en)

[origin: EP0281205A2] The overhead cable mountain railway has the cable (1) formed in a continuous loop with turn round pulleys (2,3) at each end of the loop. The cable is guided by groups of pulleys (4) to enable the cable cars to avoid any obstacles. Each cable car is attached to the cable by an arm in the form of an inverted L. The horizontal part of the arm has a clamping device to grip the cable. This horizontal part is so dimensioned that it can extend over the guide pulleys when the direction of curvature of the cable strand (6) is such that the cable lies on the side of the guide pulley (4) opposite to the vertical part of the arm which supports the cable car.

IPC 1-7

B61B 7/04; B61B 12/02; B61B 12/12

IPC 8 full level

B61B 7/04 (2006.01); **B61B 12/02** (2006.01); **B61B 12/12** (2006.01)

CPC (source: EP)

B61B 7/04 (2013.01); **B61B 12/026** (2013.01); **B61B 12/122** (2013.01)

Cited by

AU703175B2; CH678841A5; AT404015B; FR3050425A1; RU2707975C1; US11001276B2; EP3650300A1; WO2020099247A1; WO2017182736A1; US8408141B2; US8573132B2; US8474743B2; US8590458B2; US8844446B2; US9463811B2; US8393276B2; US8534196B2; US9333876B2; US7891300B2; US8082853B2; US8991317B2; US9738290B2

Designated contracting state (EPC)

AT CH DE ES FR LI SE

DOCDB simple family (publication)

EP 0281205 A2 19880907; EP 0281205 A3 19890322; EP 0281205 B1 19911113; AT E69414 T1 19911115; DE 3866130 D1 19911219; ES 2026992 T3 19920516; IT 1207747 B 19890601; IT 8704806 A0 19870306

DOCDB simple family (application)

EP 88200391 A 19880302; AT 88200391 T 19880302; DE 3866130 T 19880302; ES 88200391 T 19880302; IT 480687 A 19870306