

Title (en)
TWO-SHAFT MACHINE

Publication
EP 0281654 B1 19910417 (DE)

Application
EP 87103508 A 19870311

Priority
EP 87103508 A 19870311

Abstract (en)
[origin: EP0281654A1] In order to adapt a two-shaft machine with a housing (2) and two pistons (6, 7), which are arranged such that they can rotate in the housing without making contact, to its field of operation, it is proposed to use coated pistons and to achieve the desired cold play by selection of the coating thickness. <IMAGE>

IPC 1-7
F01C 1/12

IPC 8 full level
F04C 18/18 (2006.01); **F01C 1/08** (2006.01); **F01C 1/12** (2006.01); **F01C 1/18** (2006.01); **F01C 21/08** (2006.01); **F04C 29/00** (2006.01)

CPC (source: EP US)
F01C 1/082 (2013.01 - EP US); **F01C 1/126** (2013.01 - EP US); **Y10T 29/49236** (2015.01 - EP US); **Y10T 29/49242** (2015.01 - EP US); **Y10T 29/4984** (2015.01 - EP US)

Cited by
EP0378009A3; DE4300274A1; AT397134B; US5275205A; GB2243189A; US5223052A; GB2243189B; WO9416228A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0281654 A1 19880914; EP 0281654 B1 19910417; DE 3769468 D1 19910523; JP S63230902 A 19880927; US 4974318 A 19901204

DOCDB simple family (application)
EP 87103508 A 19870311; DE 3769468 T 19870311; JP 4242288 A 19880226; US 45838489 A 19891228