

Title (en)

FLAME ARRESTOR AND METHOD OF MANUFACTURE

Publication

EP 0283690 B1 19920819 (EN)

Application

EP 88101880 A 19880209

Priority

US 2991687 A 19870325

Abstract (en)

[origin: EP0283690A2] The invention teaches a method of spacing the elements (20, 16) of a flame arrestor and securing that spacing in a simple and economical manner. A shim (12) is used to space the elements (20, 16), the elements (20, 16) are welded together and the shim (12) is removed. This leaves a controlled flow path between the elements (20, 16) but the spacing is such to prevent the propagation of a flame through the arrestor.

IPC 1-7

A62C 4/00

IPC 8 full level

A62C 4/00 (2006.01)

CPC (source: EP)

A62C 4/00 (2013.01)

Cited by

WO9732130A1

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

EP 0283690 A2 19880928; EP 0283690 A3 19890823; EP 0283690 B1 19920819; AU 1238488 A 19880929; AU 607741 B2 19910314;
BR 8801239 A 19881025; CA 1299036 C 19920421; DE 3873796 D1 19920924; DE 3873796 T2 19930204; ES 2033949 T3 19930401;
JP S6458273 A 19890306; MX 172293 B 19931213

DOCDB simple family (application)

EP 88101880 A 19880209; AU 1238488 A 19880229; BR 8801239 A 19880318; CA 562354 A 19880324; DE 3873796 T 19880209;
ES 88101880 T 19880209; JP 6834288 A 19880324; MX 1089688 A 19880325