

Title (en)
SCROLL-TYPE DISPLACEMENT MACHINE

Publication
EP 0284774 B1 19910109 (DE)

Application
EP 88102699 A 19880224

Priority
CH 110887 A 19870324

Abstract (en)
[origin: US4861244A] In a displacement machine for compressible media on the spiral principle, the rotor disk (2) terminates radially flush with the displacement strips (3, 3'). So that the disk (2) can pass through the housing, in the inlet region (12, 12') of the machine the inner web (18, 18') of one housing half (7) is lowered by the amount of the disk thickness. To prevent leaks during the operation of the machine, the transition (19, 19') between the raised web (17, 17') and the lowered web (18, 18') is made circular. The rounding cooperates with a clearance (20, 20') in the form of an arc of a circle in the disk (2). Machines of this type are especially suitable for the supercharging of internal-combustion engines.

IPC 1-7
F01C 1/02

IPC 8 full level
B65G 33/26 (2006.01); **F01C 1/02** (2006.01); **F04C 18/02** (2006.01)

CPC (source: EP US)
F01C 1/0276 (2013.01 - EP US)

Cited by
AU682641B2; EP0547491A1; EP0545188A1; DE102007043674B4; DE102007043674A1; US8425211B2; WO2009023974A1

Designated contracting state (EPC)
AT CH DE ES FR GB IT LI

DOCDB simple family (publication)
EP 0284774 A1 19881005; EP 0284774 B1 19910109; AT E59880 T1 19910115; BR 8801295 A 19881025; CH 673874 A5 19900412; DE 3861482 D1 19910214; ES 2023227 B3 19920101; JP 2545432 B2 19961016; JP H01249973 A 19891005; US 4861244 A 19890829

DOCDB simple family (application)
EP 88102699 A 19880224; AT 88102699 T 19880224; BR 8801295 A 19880323; CH 110887 A 19870324; DE 3861482 T 19880224; ES 88102699 T 19880224; JP 6835088 A 19880324; US 16822688 A 19880315