

Title (en)

PROFILE TO JOIN A COAT OF PLASTER TO A DOOR FRAME, A WINDOW FRAME OR THE LIKE

Publication

EP 0288673 A3 19890503 (DE)

Application

EP 88102132 A 19880213

Priority

DE 3714191 A 19870429

Abstract (en)

[origin: EP0288673A2] In a profile to join a coat of plaster, applied to a wall soffit, to frames, such as door or window frames, having an approximately U-shaped hollow profile, the height of which is chosen to correspond to the thickness of the coat of plaster and the width of which is chosen to correspond to the joint between the coat of plaster and frame, the outer leg (4) opposite the frame (20) is inclined at an obtuse angle of about 100 DEG to the fastening flange (3, 13). As a result of the outwardly inclined outer leg, the profile bears resiliently and thus positively and non-positively against an adjoining frame. The sealing action between the profile and the frame is thus improved to such an extent that stresses and strains between the profile and the frame are compensated. <IMAGE>

IPC 1-7

E04F 19/02

IPC 8 full level

E04F 13/06 (2006.01); **E04F 19/02** (2006.01); **E06B 1/62** (2006.01)

CPC (source: EP)

E04F 13/06 (2013.01); **E06B 1/62** (2013.01); **E04F 2013/063** (2013.01); **E04F 2013/066** (2013.01); **E06B 2001/624** (2013.01)

Citation (search report)

- [A] DE 8600241 U1 19860313
- [A] DE 3420897 A1 19851205 - MAISCH F PROTEKTORWERK [DE]
- [A] GB 2096060 A 19821013 - ROBERTS TERENCE JOHN
- [A] FR 2369446 A1 19780526 - GILLOT MARCEL [FR]

Cited by

EP1205611A3; EP0943749A1; EP0699811A1; KR102053650B1; US8099911B2; WO2008085067A1

Designated contracting state (EPC)

AT BE CH FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0288673 A2 19881102; **EP 0288673 A3 19890503**; **EP 0288673 B1 19911016**; AT E68548 T1 19911115; DE 3714191 A1 19881117;
DE 3714191 C2 19960418

DOCDB simple family (application)

EP 88102132 A 19880213; AT 88102132 T 19880213; DE 3714191 A 19870429