

Title (en)
POTENTIOMETER

Publication
EP 0288930 B1 19930407 (DE)

Application
EP 88106506 A 19880422

Priority
DE 3714348 A 19870429

Abstract (en)
[origin: EP0288930A2] The potentiometer, which is intended to be mounted on heavily vibrating objects such as the engine block of an internal-combustion engine, has an outer housing (10), which is mounted on the object, and an inner housing (20) which is arranged generally in the interior of the outer housing (10). The two housings are connected to one another by means of at least one elastically sprung damping element (27), for example a rubber O-ring, thus, however, being decoupled to the greatest possible extent in vibration terms. <IMAGE>

IPC 1-7
F02D 41/00; H01C 1/022; H01C 10/30

IPC 8 full level
F02D 41/00 (2006.01); **H01C 1/022** (2006.01); **H01C 10/30** (2006.01)

CPC (source: EP US)
H01C 1/022 (2013.01 - EP US); **H01C 10/30** (2013.01 - EP US)

Designated contracting state (EPC)
AT DE FR GB IT SE

DOCDB simple family (publication)
EP 0288930 A2 19881102; EP 0288930 A3 19900110; EP 0288930 B1 19930407; AT E88035 T1 19930415; DE 3714348 A1 19881117;
DE 3714348 C2 19901025; DE 3879998 D1 19930513; US 4894638 A 19900116; YU 40888 A 19901231

DOCDB simple family (application)
EP 88106506 A 19880422; AT 88106506 T 19880422; DE 3714348 A 19870429; DE 3879998 T 19880422; US 18777588 A 19880429;
YU 40888 A 19880301