

Title (en)
ROLL-UP BLIND

Publication
EP 0289076 A3 19890503 (FR)

Application
EP 88200734 A 19880418

Priority
BE 8700459 A 19870428

Abstract (en)
[origin: EP0289076A2] The blind consists of a spring-loaded roller (1) for the blind, with the cable reels (4, 5) at its ends. A rigid element (8) is attached to the free end of the blind (6), which controls the tension of the blind, is located inside the roller (1), which also contains a control element (12) in the form of an electric motor. The torsion spring, which is in the form of a spiral spring, is connected at one end to a bearing element (21) on a shaft (18) and at the other to one of the cable reels (5).

IPC 1-7
E06B 9/204; **E06B 9/08**

IPC 8 full level
E06B 9/40 (2006.01); **E06B 9/68** (2006.01)

CPC (source: EP)
E04F 10/0607 (2013.01); **E04F 10/0648** (2013.01); **E04F 10/0655** (2013.01); **E06B 9/40** (2013.01); **E06B 9/62** (2013.01); **E06B 9/68** (2013.01); **E04F 10/0692** (2013.01); **E06B 2009/583** (2013.01)

Citation (search report)
• [Y] US 3279528 A 19661018 - GAMBON JOHN M, et al
• [Y] EP 0082302 A1 19830629 - REFLEXA WERKE H P ALBRECHT [DE]
• [A] FR 2570119 A1 19860314 - FILTRASOL [FR]
• [A] FR 2559527 A1 19850816 - AQUITAINE FERMETURES SARL [FR]

Cited by
FR2663675A1; DE4224815A1; FR2645202A1; EP4365401A1; ES2154142A1; CN110500022A; EP1319772A1; FR2692930A1; DE4024666A1; WO9957407A1; WO9012190A1

Designated contracting state (EPC)
BE DE FR GB LU NL

DOCDB simple family (publication)
EP 0289076 A2 19881102; **EP 0289076 A3 19890503**; BE 1000507 A7 19890103

DOCDB simple family (application)
EP 88200734 A 19880418; BE 8700459 A 19870428