

Title (en)

APPARATUS FOR RELEASING A DEFECTIVE WEFT YARN FROM THE SHED OF A LOOM

Publication

EP 0290383 B1 19910605 (DE)

Application

EP 88810245 A 19880418

Priority

CH 177287 A 19870508

Abstract (en)

[origin: US4899788A] The arrangement for removing a faulty weft yarn from a shed comprises a manipulator for physically moving a yarn clamp carrier between a rest position and a yarn clamping position for engaging a weft yarn. A needle is provided on the carrier for releasing the weft yarn from the beat-up line of the cloth for delivery into the yarn clamp. A rotatable storage drum at a yarn release position winds on yarn from the yarn clamp for subsequent delivery to a suction tube for removal.

IPC 1-7

D03D 51/08

IPC 8 full level

D03D 51/00 (2006.01); **D03D 51/08** (2006.01)

CPC (source: EP US)

D03D 51/085 (2013.01 - EP US)

Cited by

DE3843399A1; US4974640A; EP0405359A1; WO9106696A1

Designated contracting state (EPC)

BE CH DE FR IT LI

DOCDB simple family (publication)

EP 0290383 A1 19881109; **EP 0290383 B1 19910605**; BR 8802222 A 19881206; DE 3863120 D1 19910711; JP S63288248 A 19881125; US 4899788 A 19900213

DOCDB simple family (application)

EP 88810245 A 19880418; BR 8802222 A 19880506; DE 3863120 T 19880418; JP 11027188 A 19880506; US 19088088 A 19880506