

Title (en)

BOGIE FOR RAILWAY VEHICLES, ESPECIALLY FOR TRAMS

Publication

EP 0290782 B1 19910508 (DE)

Application

EP 88105504 A 19880407

Priority

DE 3715633 A 19870511

Abstract (en)

[origin: EP0290782A1] In order to be able to realise, in particular in trams, a floor of low constructional height even in the region of the bogies, a centre cross carrier (1a) of the bogie frame (1) is lowered down to the rail upper edge (S.O.) to such an extent that there is a free space between the said carrier (1a) and the lower edge of a carriage-side, low-lying centre aisle (4c). This free space is penetrated in the case of a first design (Fig. 1A) of the main cross carrier (4a) of the carriage body (4), in which case a ball-type steering ring (3) is provided between the main cross carrier (4) and the bogie frame (1). In a second design (Fig. 1B), the free space serves essentially for the arrangement and the deflections of a longitudinal connecting link (5) which engages on the bogie frame (1) and on the carriage body; on each longitudinal side a pneumatic spring (2) is arranged between the frame (1) and the upper internal wall of the main cross carrier (4a) which is hat-shaped in the second design. <IMAGE>

IPC 1-7

B61D 13/00; B61F 5/02; B61F 5/16; B61F 5/52

IPC 8 full level

B61D 13/00 (2006.01); **B61F 5/02** (2006.01); **B61F 5/16** (2006.01); **B61F 5/52** (2006.01)

CPC (source: EP)

B61D 13/00 (2013.01); **B61F 5/02** (2013.01); **B61F 5/16** (2013.01); **B61F 5/52** (2013.01)

Citation (examination)

DE 1010092 B 19570613 - VER WESTDEUTSCHE WAGGONFAB

Cited by

CN104890693A; EP0687613A1; EP0598353A1; AU662659B2

Designated contracting state (EPC)

AT CH DE FR GB LI NL

DOCDB simple family (publication)

EP 0290782 A1 19881117; EP 0290782 B1 19910508; AT E63269 T1 19910515; DE 3715633 A1 19881124; DE 3862678 D1 19910613

DOCDB simple family (application)

EP 88105504 A 19880407; AT 88105504 T 19880407; DE 3715633 A 19870511; DE 3862678 T 19880407