

Title (en)  
RECORD CARRIER PRINTING METHOD

Publication  
**EP 0290845 B1 19930818 (DE)**

Application  
**EP 88106548 A 19880423**

Priority  
DE 3715523 A 19870509

Abstract (en)  
[origin: US4828408A] In a transfer printer, the printed, ribbon-like information carrier is suddenly separated from the printing ink ribbon 1 to 5 mm after the two ribbons have passed the transfer pins. Separation is gently initiated over a brief length before this.

IPC 1-7  
**B41J 2/325**

IPC 8 full level  
**B41J 2/325** (2006.01); **B41J 17/38** (2006.01); **B41J 35/04** (2006.01); **B65C 1/00** (2006.01); **B65C 9/46** (2006.01)

CPC (source: EP US)  
**B41J 17/38** (2013.01 - EP US)

Cited by  
DE3935348A1; DE3935347A1; EP0669589A1; FR2716411A1; US5739835A; EP1839861B2

Designated contracting state (EPC)  
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0290845 A2 19881117; EP 0290845 A3 19900404; EP 0290845 B1 19930818**; AT E93188 T1 19930915; AU 1566688 A 19881110; AU 597820 B2 19900607; CA 1296949 C 19920310; DE 3715523 A1 19881117; DE 3883284 D1 19930923; DE 8813536 U1 19890202; JP S63307971 A 19881215; NZ 224516 A 19900426; US 4828408 A 19890509

DOCDB simple family (application)  
**EP 88106548 A 19880423**; AT 88106548 T 19880423; AU 1566688 A 19880506; CA 566130 A 19880506; DE 3715523 A 19870509; DE 3883284 T 19880423; DE 8813536 U 19880423; JP 11230188 A 19880509; NZ 22451688 A 19880506; US 19258588 A 19880509