

Title (en)

TUNNEL KILN FOR BURNING LIGHT BRICKS CONTAINING A HIGH PERCENTAGE OF COMBUSTIBLE AND VOLATILE COMPONENTS

Publication

**EP 0291631 B1 19920624 (DE)**

Application

**EP 88101735 A 19880206**

Priority

DE 3717320 A 19870522

Abstract (en)

[origin: EP0291631A2] A tunnel furnace is described, with preheating chamber and combustion chamber which are separated from one another by a gate, and with a degassing zone, consisting of a gas circulating circuit, heated indirectly by the smoke gases, for degassing the combustible volatile components and a combustion device for the outgassed volatile components. In this connection, the degassing zone is assigned to the preheating chamber (3), the gases being removed from suction openings (5) in the vicinity of the chamber entrance (6) by means of a fan (4) and fed back in again in front of the gate (2) to the combustion chamber (1). Also connected in this circulating circuit are two heating stages (8, 10), there being provided after the first heating stage (8) a branch for a part of the circulating gases, which opens into the pipe of the smoke gases carried off, in which branch the post-combustion device (9) and subsequently a heat exchanger, which serves as second heating stage (10) for the circulating gases, are connected. <IMAGE>

IPC 1-7

**F27B 9/30; F27D 17/00**

IPC 8 full level

**F27B 9/30** (2006.01); **F27D 17/00** (2006.01)

CPC (source: EP)

**F27B 9/3005** (2013.01); **F27D 17/001** (2013.01)

Cited by

DE3923887A1; FR3005723A1; WO2014184455A1

Designated contracting state (EPC)

AT FR

DOCDB simple family (publication)

**EP 0291631 A2 19881123; EP 0291631 A3 19900321; EP 0291631 B1 19920624**; AT E77688 T1 19920715; DE 3717320 C1 19880714

DOCDB simple family (application)

**EP 88101735 A 19880206**; AT 88101735 T 19880206; DE 3717320 A 19870522