Title (en)

PROCESS FOR THE CONSTRUCTION OF A DORMER WINDOW, AND A BUILDING KIT INTENDED FOR CARRYING OUT SAID PROCESS

Publication

EP 0292068 B1 19910731 (EN)

Application

EP 88200986 A 19880517

Priority

NL 8701187 A 19870518

Abstract (en)

[origin: EP0292068A1] In a proces for the construction of a dormer window, a rectangular piece is sawn out of the roof boarding while sawing through the purlins (2) present there and a cheek (3) is fixed along the two slanting boundaries of the hole formed in such a way that two congruent triangles project from the roof face, a window frame (5) is fixed between or against the cheeks (3) and a roof section is placed on the cheeks. Finally the joint round the opening in the roof boarding is sealed. To simplify the fitting of the dormer window the bottom edge of the cheeks is provided with a trimming joist which is fixed against the sawn faces of the purlins (2) which have been sawn through. Preferably a groove is provided in the top edge of the trimming joist and in the bottom edge of the cheeks (3), and wedge pieces are slid into opposite grooves of trimming joists and cheeks. The trimming joists are made flush with the bottom face of the roof boarding and are fixed in this position. The wedge pieces are fixed in a position in which the bottom edge thereof projects slightly beyond the tile laths and the bottom edge of the cheeks is flush with the top edge of the tile laths.

IPC 1-7

E04B 7/18

IPC 8 full level

E04B 7/18 (2006.01)

CPC (source: EP)

E04B 7/18 (2013.01)

Cited by

BE1021723B1; CN110728023A; AU695569B2

Designated contracting state (EPC)

AT BE DE FR GB LU NL SE

DOCDB simple family (publication)

EP 0292068 A1 19881123: EP 0292068 B1 19910731: AT E65816 T1 19910815: DE 3863969 D1 19910905: NL 8701187 A 19881216

DOCDB simple family (application)

EP 88200986 A 19880517; AT 88200986 T 19880517; DE 3863969 T 19880517; NL 8701187 A 19870518