

Title (en)
PRINTING APPARATUS

Publication
EP 0292492 B1 19930623 (EN)

Application
EP 87901086 A 19870203

Priority
GB 8602561 A 19860203

Abstract (en)
[origin: WO8704665A1] The apparatus comprises a plate cylinder (15), a blanket cylinder(16) and an impression cylinder (17). A web (W) passes between the blanket and impression cylinder to enable print to be applied to the web by the blanket cylinder. The plate and blanket cylinders (15, 16) are provided as a one-piece cartridge movable axially to a position offset from the web. The impression cylinder (17) is also movable independently of the other cylinders to a position offset from the web to enable the impression cylinder to be changed without breaking the web or removing the web from the apparatus.

IPC 1-7
B41F 13/24; B41F 13/44

IPC 8 full level
B41F 13/24 (2006.01); **B41F 13/44** (2006.01)

CPC (source: EP)
B41F 13/24 (2013.01); **B41F 13/44** (2013.01); **B41P 2217/11** (2013.01); **B41P 2217/13** (2013.01)

Designated contracting state (EPC)
BE DE FR GB IT NL SE

DOCDB simple family (publication)
WO 8704665 A1 19870813; AU 599631 B2 19900726; AU 6934887 A 19870825; DE 3786349 D1 19930729; DE 3786349 T2 19940217; EP 0292492 A1 19881130; EP 0292492 B1 19930623; GB 8602561 D0 19860312

DOCDB simple family (application)
GB 8700077 W 19870203; AU 6934887 A 19870203; DE 3786349 T 19870203; EP 87901086 A 19870203; GB 8602561 A 19860203