

Title (en)

A RESILIENT TENSIONER DEVICE FOR A JACQUARD MACHINE

Publication

**EP 0292632 A3 19900131 (EN)**

Application

**EP 87830279 A 19870717**

Priority

IT 2072987 A 19870529

Abstract (en)

[origin: EP0292632A2] A resilient tensioner device (1) for a Jacquard machine for the production of Jacquard weaves, comprises a sheath (2) the upper end of which is connected to an upper filiform element (3) which can be hooked onto the wires (4) of the Jacquard machine which are slidable in upper guide battens (6). In the sheath (2) is housed a tension spring (15) operatively connected to a lower filiform element (16) projecting from the sheath (2) and provided at its free end with coupling means (20,21,22) for anchorage to a lower batten (18).

IPC 1-7

**D03C 3/24**; **D03C 3/44**

IPC 8 full level

**D03C 3/24** (2006.01); **D03C 3/44** (2006.01)

CPC (source: EP)

**D03C 3/24** (2013.01); **D03C 3/44** (2013.01)

Citation (search report)

- [X] EP 0094270 A2 19831116 - RINET JEAN MICHEL [FR], et al
- [A] DE 2828140 A1 19800110 - REMY WILMS FA
- [A] GB 2001355 A 19790131 - WIRKMASCHINENBAU KARL MARX VEB
- [A] DE 2651057 A1 19780511 - SCHNITZLER & VOGEL
- [A] DE 291001 C

Cited by

EP0472904A1; EP1130143A1; CN106687629A; FR2759095A1; US6216748B1; US6318415B1; US6216749B1; EP0533636A1; EP0893521A1; FR2766501A1; BE1015048A4; EP1382726A3; US6367512B2; US7025094B2; WO9835080A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB LI NL

DOCDB simple family (publication)

**EP 0292632 A2 19881130**; **EP 0292632 A3 19900131**; IT 1204672 B 19890310; IT 8720729 A0 19870529

DOCDB simple family (application)

**EP 87830279 A 19870717**; IT 2072987 A 19870529