

Title (en)
DOT MATRIX PRINT HEAD DRIVE METHOD

Publication
EP 0294288 B1 19930915 (EN)

Application
EP 88401330 A 19880601

Priority
JP 13773387 A 19870602

Abstract (en)
[origin: EP0294288A2] In a dot matrix print head drive method for controlling head drive signals for driving dot pins in accordance with print pattern signals, a correction factor is set specifically to each dot pin; and the length of time for which the print pattern signals are to remain in effects is varied according to the correction factor, to correct the drive time for each dot pin.

IPC 1-7
B41J 2/23; **B41J 2/30**; **B41J 7/92**

IPC 8 full level
B41J 2/51 (2006.01); **B41J 2/30** (2006.01)

CPC (source: EP)
B41J 2/30 (2013.01)

Cited by
EP0391867A3; US5956052A; EP0446045A3; US5356228A; EP0380352A3; US5099383A; EP0539210A3; US5330277A; US6231155B1; EP1343304B1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0294288 A2 19881207; **EP 0294288 A3 19900613**; **EP 0294288 B1 19930915**; DE 3884056 D1 19931021; DE 3884056 T2 19940217; JP 2520909 B2 19960731; JP S63302060 A 19881208

DOCDB simple family (application)
EP 88401330 A 19880601; DE 3884056 T 19880601; JP 13773387 A 19870602