

Title (en)

METHOD AND DEVICE FOR PIECING A YARN IN A FRICTION-SPINNING DEVICE

Publication

EP 0294795 B1 19911127 (DE)

Application

EP 88109159 A 19880608

Priority

CH 220887 A 19870612

Abstract (en)

[origin: EP0294795A1] A method for piecing a yarn in a friction-spinning device is characterised in that a package (12) wound on a friction spinning means to a predetermined size is conveyed during piecing by an airstream past a yarn draw off means (6) which in the draw off direction has been arranged downstream of the friction spinning means, and in that the subsequent yarn (5) of adequate strength is introduced into the yarn draw off means (6) after the airstream has been interrupted. This ensures reliable introduction of the yarn (5) into the yarn draw off means (6) and prevents breaking of the yarn (5). Piecing can take place at the normal production speed. <IMAGE>

IPC 1-7

D01H 4/48

IPC 8 full level

D01H 4/52 (2006.01)

CPC (source: EP US)

D01H 4/52 (2013.01 - EP US)

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0294795 A1 19881214; EP 0294795 B1 19911127; DE 3866431 D1 19920109; JP S63315626 A 19881223; US 4918913 A 19900424

DOCDB simple family (application)

EP 88109159 A 19880608; DE 3866431 T 19880608; JP 14384788 A 19880613; US 20306188 A 19880606