

Title (en)

Minimizing residual charge carryover in an asynchronous raster input scanner.

Title (de)

Herabsetzung des Rückstandsladungstransfers in einem asynchronen Rastereingangsbaster.

Title (fr)

Réduction au minimum du transfert de charges résiduelles dans un dispositif asynchrone d'analyse de trames d'entrée.

Publication

EP 0295875 A2 19881221 (EN)

Application

EP 88305433 A 19880615

Priority

US 6174787 A 19870615

Abstract (en)

A method and apparatus for minimizing residual charges in the shift registers of a CCD type scanning array (35) in an asynchronously operated image input terminal (10). The unknown arrival time of the next integration signal is predicted and, based on that prediction, the last periodic dumping pulse before the integration signal is delayed a required period of time to assure clearing of residual charges from the shift registers.

IPC 1-7

H04N 1/40

IPC 8 full level

H01L 27/148 (2006.01); **H04N 1/40** (2006.01); **H04N 5/235** (2006.01); **H04N 5/353** (2011.01); **H04N 5/359** (2011.01); **H04N 5/372** (2011.01)

CPC (source: EP US)

H04N 1/40056 (2013.01 - EP US); **H04N 23/73** (2023.01 - EP US); **H04N 25/626** (2023.01 - EP US)

Cited by

EP0411954A3; EP1081933A3; US2015024108A1; US10390552B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

US 4771333 A 19880913; DE 3854486 D1 19951026; DE 3854486 T2 19960502; EP 0295875 A2 19881221; EP 0295875 A3 19901128; EP 0295875 B1 19950920; JP H07114473 B2 19951206; JP S6410789 A 19890113

DOCDB simple family (application)

US 6174787 A 19870615; DE 3854486 T 19880615; EP 88305433 A 19880615; JP 14033488 A 19880607