

Title (en)

Permanent mould for continuous casting of preliminary sections for beam rolling.

Title (de)

Kokille zum Stranggießen von Vorprofilen zur Trägerwalzung.

Title (fr)

Coquille pour la coulée continue de profiles d'entrées pour laminage de poutrelles.

Publication

**EP 0297258 A2 19890104 (DE)**

Application

**EP 88107714 A 19880513**

Priority

DE 3721266 A 19870627

Abstract (en)

[origin: JPS6422451A] PURPOSE: To enable the adjustment of a web height, web thickness and flange thickness of a preform body for rolling a beam by arranging straight-end range and curving end range to the outside in each side wall of a mold and enabling the adjustment of the side walls in the horizontal direction to casting direction. CONSTITUTION: The mold is formed of two side walls 1, 2 and two end walls 3, 4 arranged between these side walls 1, 2. In order to form a casting chamber for preform body 5 to roll the beam, the side walls 1, 2 have the curving end ranges and the straight end ranges. These end ranges are arranged in the reverse direction and the chamber for flanges 6, 7 of the preform body 5 is formed together with the end walls 3, 4 arranged between these side walls. The side walls 1, 2 of the mold are mutually paralleled and can adjust in the horizontal direction to the casting direction along the directions of the arrow marks 17, 18. By this constitution, the height of the web 9 in the preform body 5 can be changed.

Abstract (de)

Bei einer Kokille zum Stranggießen von aus einem Steg (9) und zwei Flanschen (6, 7) bestehenden Vorprofilen (5) zur Herstellung von vorzugsweise Stahlträgern mit zwei über den Steg (9) und die Flanschen (6, 7) reichenden Seitenwänden (1, 2) bestimmen die zwischen den Seitenwänden (1, 2) verstellbar angeordneten Stirnwände (3, 4) die Flanschdicke. Zur Schaffung einer Stranggießkokille unabhängig voneinander einstellbaren Steghöhe, Stegdicke und Flanschdicke weist jede Seitenwand (1, 2) einen geraden und einen nach außen abgewinkelten Endbereich (1a, 1b, 2a, 2b) auf, wobei die Stirnwände (3, 4) zwischen den gegenüberstehenden geraden und abgewinkelten Endbereichen (1b, 2a und 2a, 1b) angeordnet sind und mindestens eine Seitenwand (1, 2) in Richtung ihrer ebenen Fläche gegenüber der anderen Seitenwand (1, 2) quer zur Gießrichtung (17, 18) verstellbar ist.

IPC 1-7

**B22D 11/04**

IPC 8 full level

**B22D 11/00** (2006.01); **B22D 11/04** (2006.01); **B22D 11/05** (2006.01)

CPC (source: EP US)

**B22D 11/0406** (2013.01 - EP US)

Cited by

US7427526B2; EP0563551A1; DE3709188A1; US5082746A; EP0478741A4; CN1083307C; TR28532A; US7309620B2

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0297258 A2 19890104**; **EP 0297258 A3 19900117**; **EP 0297258 B1 19920408**; AT E74543 T1 19920415; CA 1314117 C 19930309; DE 3721266 A1 19890112; DE 3869840 D1 19920514; JP S6422451 A 19890125; US 4881589 A 19891121

DOCDB simple family (application)

**EP 88107714 A 19880513**; AT 88107714 T 19880513; CA 570134 A 19880622; DE 3721266 A 19870627; DE 3869840 T 19880513; JP 15701788 A 19880627; US 21175788 A 19880627